

## PRODUCT-DETAILS

# 263BU6W

## Ind. P&S#263BU6W



### General Information

|                       |                                                                                                                                                                      |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 263BU6W                                                                                                                                                              |
| Product ID            | 2CMA168104R1000                                                                                                                                                      |
| EAN                   | 7392696681049                                                                                                                                                        |
| Catalog Description   | Ind. P&S#263BU6W                                                                                                                                                     |
| Long Description      | Inlet, panel mounting, earthing sleeve position 6h, rated current 63A, IP67 watertight, unified flange, straight, 2-poles+earth, frequency 50-60 Hz, color code Blue |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2417405            |
| E-Number (Finland)     | 2421573             |
| E-Number (Norway)      | 2417405             |
| EAN                    | 7392696681049       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 114 mm |
| Product Net Height | 114 mm |

|                    |        |
|--------------------|--------|
| Product Net Weight | 0.5 kg |
|--------------------|--------|

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 112 mm                  |
| Package Level 1 Depth / Length | 112 mm                  |
| Package Level 1 Height         | 139 mm                  |
| Package Level 1 Gross Weight   | 0.5 kg                  |
| Package Level 1 EAN            | 7392696681049           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 195 kg                  |
| Package Level 2 EAN            | 7392696076098           |
| Package Level 2 Units          | pallet (lift) 350 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| CB Certificate                 | 2CHC660163X0201 |
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1519130         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                                                 |
|------------------------|-------------------------------------------------|
| Additional Information | 2P+E                                            |
| Ambient Temperature    | -25 ... 40 °C                                   |
| Cable Cross-Section    | 6 ... 25 mm²                                    |
| Color                  | Blue                                            |
| Connection Type        | Screw                                           |
| Degree of Protection   | IP67<br>IP69                                    |
| Design                 | Surface mounted plug                            |
| Frequency (f)          | 50 Hz<br>60 Hz                                  |
| Function               | Inlet, panel mounting, unified flange, straight |
| Housing Material       | Thermoplastic (PBT)                             |

|                            |                                  |
|----------------------------|----------------------------------|
| Invoice Description        | Ind. P&S#263BU6W                 |
| Mounting Holes             | 61x61                            |
| Mounting Type              | unified flange, straight         |
| Number of Poles            | 3                                |
| Order Multiple             | 1 piece                          |
| Product Main Type          | TBU                              |
| Product Name               | Panel mounted inlet              |
| Protection Type            | Watertight                       |
| Rated Current ( $I_n$ )    | 63 A                             |
| Rated Frequency (f)        | 50...60 Hz                       |
| Rated Voltage ( $U_r$ )    | 200 ... 250 V                    |
| Recommended Screw Driver   | PH2                              |
| Standards                  | IEC 60309-1, -2                  |
| Suitable For               | Inlets for Panel Mounting        |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC000040M0001                  |
| Installation Manual        | 2CMC000040M0001                  |
| RAL Number                 | RAL 7001 - Silver Grey           |

Classifications

|        |          |
|--------|----------|
| eClass | 27440519 |
| UNSPSC | 39120000 |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Inlets for Panel Mounting

