


PRODUCT-DETAILS

416BUFV6

Phase sequence changer inlet, 6h, 16A, IP44,
3P+N+E



General Information

Extended Product Type	416BUFV6
Product ID	2CMA168159R1000
EAN	7392696681599
Catalog Description	Phase sequence changer inlet, 6h, 16A, IP44, 3P+N+E
Long Description	Phase sequence changer inlet, 6h, 16A, IP44, 3P+N+E Clock Position Of Grounding Contact 6 hour Color code Red, Use flexible connection cables, that comply with the requirements in 60245 IEC 53 or 60245 IEC 66. The cable conductors should be mounted with slack to permit the inverting operation.

Ordering

E-Number (Sweden)	2416004
EAN	7392696681599
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	66 mm
Product Net Height	70 mm
Product Net Weight	0.19 kg

Container Information

Package Level 1 Width	138 mm
Package Level 1 Depth / Length	158 mm
Package Level 1 Height	345 mm
Package Level 1 Gross Weight	1.9 kg
Package Level 1 EAN	7392696681933
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	146 kg
Package Level 2 Units	pallet (lift) 660 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate	2CHC660152X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614202
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Color	Red
Connection Type	Screw Clamp
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Panel mounted inlet with phase inverter
Housing Material	Plastic (PA)
Invoice Description	IND. P&S#416BUFV6
Mounting Holes	51x51
Number of Poles	5

Order Multiple	10 piece
Product Main Type	EBUFV
Product Name	Phase inverter plugs
Protection Type	Splashproof
Rated Current (I_n)	16 A
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	416BUFV6
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700041M0002
Installation Manual	2CMC710006K0001, 2CMC700041M0002
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440524
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Special Plugs & Sockets → Phase Sequence Products

