

PRODUCT-DETAILS

416BSFV6

Phase sequence changer surface inlet, 6h, 16A, IP44, 3P+N+E



General Information

Extended Product Type	416BSFV6
Product ID	2CMA168169R1000
EAN	7392696681698
Catalog Description	Phase sequence changer surface inlet, 6h, 16A, IP44, 3P+N+E
Long Description	Phase sequence changer surface inlet, 6h, 16A, IP44, 3P+N+E Clock Position Of Grounding Contact 6 hour Color code Red, Use flexible connection cables, that comply with the requirements in 60245 IEC 53 or 60245 IEC 66. The cable conductors should be mounted with slack to permit the inverting operation.

Ordering

E-Number (Sweden)	2416003
EAN	7392696681698
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	79 mm
Product Net Height	81 mm
Product Net Weight	0.19 kg

Container Information

Package Level 1 Width	154 mm
Package Level 1 Depth / Length	182 mm
Package Level 1 Height	378 mm
Package Level 1 Gross Weight	1.9 kg
Package Level 1 EAN	7392696681940
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	106 kg
Package Level 2 Units	pallet (lift) 450 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate	2CHC660152X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614202
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Color	Red
Connection Type	Screw Clamp
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Wall mounted inlet with phase inverter
Housing Material	Plastic (PA)
Invoice Description	IND. P&S#416BSFV6
Mounting Holes	91x67
Number of Poles	5

Order Multiple	10 piece
Product Main Type	EBSFV
Product Name	Phase inverter plugs
Protection Type	Splashproof
Rated Current (I_n)	16 A
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	416BSFV6
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700058M0001
Installation Manual	2CMC710006K0001, 2CMC700041M0002
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440524
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Special Plugs & Sockets → Phase Sequence Products

