

## PRODUCT-DETAILS

# 316RL4W

Surface socket-outlet for looping, 4h, 16A, IP67, 3P+E



## General Information

|                       |                                                                                                                                                          |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 316RL4W                                                                                                                                                  |
| Product ID            | 2CMA168464R1000                                                                                                                                          |
| EAN                   | 7392696684644                                                                                                                                            |
| Catalog Description   | Surface socket-outlet for looping, 4h, 16A, IP67, 3P+E                                                                                                   |
| Long Description      | Surface socket-outlet for looping, earthing sleeve position 4h, rated current 16A, IP67 watertight, 3-poles+earth, frequency 50-60 Hz, color code Yellow |

## Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | 2417491             |
| E-Number (Finland)     | 2420206             |
| E-Number (Norway)      | 2417491             |
| EAN                    | 7392696684644       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

## Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 120 mm |
| Product Net Height | 253 mm |
| Product Net Weight | 0.7 kg |

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 152 mm                  |
| Package Level 1 Depth / Length | 120 mm                  |
| Package Level 1 Height         | 265 mm                  |
| Package Level 1 Gross Weight   | 0.7 kg                  |
| Package Level 1 EAN            | 7392696684644           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 107.5 kg                |
| Package Level 2 EAN            | 7392696077415           |
| Package Level 2 Units          | pallet (lift) 125 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1613211         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                                 |                                      |
|---------------------------------|--------------------------------------|
| Additional Information          | 3P+E                                 |
| Ambient Temperature             | -25 ... 40 °C                        |
| Cable Cross-Section             | 2.5 ... 10 mm²                       |
| Cable Diameter                  | 13 ... 17 mm                         |
| Cable Entry Position            | Cable entry, knock-outs 2xØ25mm      |
| Color                           | Yellow                               |
| Connection Type                 | Screw                                |
| Degree of Protection            | IP67                                 |
| Frequency (f)                   | 50 Hz<br>60 Hz                       |
| Function                        | Surface socket outlet for looping    |
| Housing Material                | Thermoplastic (PBT)                  |
| Invoice Description             | Ind. P&S#316RL4W                     |
| Mounting Holes                  | 171x90                               |
| Number of Poles                 | 4                                    |
| Order Multiple                  | 1 piece                              |
| Product Main Type               | TRL                                  |
| Product Name                    | Industrial Socket Outlet for Looping |
| Protection Type                 | Watertight                           |
| Rated Current (I <sub>n</sub> ) | 16 A                                 |

|                                 |                                  |
|---------------------------------|----------------------------------|
| Rated Voltage (U <sub>r</sub> ) | 100 ... 130 V                    |
| Recommended Screw Driver        | PH2                              |
| Standards                       | IEC 60309-1, -2                  |
| Suitable For                    | Socket Outlets for Looping       |
| Suitable for Product Class      | IEC Industrial Plugs and Sockets |
| Instructions and Manuals        | 2CMC000033M0001                  |
| Installation Manual             | 2CMC000033M0001                  |
| RAL Number                      | RAL 7001 - Silver Grey           |

Classifications

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39120000 |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Looping

