

## PRODUCT-DETAILS

# 332RL5W

Surface socket-outlet for looping, 5h, 32A, IP67, 3P+E



## General Information

|                       |                                                                                                                                                         |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 332RL5W                                                                                                                                                 |
| Product ID            | 2CMA168488R1000                                                                                                                                         |
| EAN                   | 7392696684880                                                                                                                                           |
| Catalog Description   | Surface socket-outlet for looping, 5h, 32A, IP67, 3P+E                                                                                                  |
| Long Description      | Surface socket-outlet for looping, earthing sleeve position 5h, rated current 32A, IP67 watertight, 3-poles+earth, frequency 50-60 Hz, color code Black |

## Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | 2417515             |
| E-Number (Finland)     | 2421715             |
| E-Number (Norway)      | 2417515             |
| EAN                    | 7392696684880       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

## Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 120 mm |
| Product Net Height | 253 mm |

|                    |        |
|--------------------|--------|
| Product Net Weight | 0.7 kg |
|--------------------|--------|

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 152 mm                  |
| Package Level 1 Depth / Length | 120 mm                  |
| Package Level 1 Height         | 265 mm                  |
| Package Level 1 Gross Weight   | 0.8 kg                  |
| Package Level 1 EAN            | 7392696684880           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 120 kg                  |
| Package Level 2 EAN            | 7392696077095           |
| Package Level 2 Units          | pallet (lift) 125 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1613211         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                                   |
|------------------------|-----------------------------------|
| Additional Information | 3P+E                              |
| Ambient Temperature    | -25 ... 40 °C                     |
| Cable Cross-Section    | 2.5 ... 10 mm <sup>2</sup>        |
| Cable Diameter         | 13 ... 21.5 mm                    |
| Cable Entry Position   | Cable entry, knock-outs 2xØ25mm   |
| Color                  | Black                             |
| Connection Type        | Screw                             |
| Degree of Protection   | IP67                              |
| Frequency (f)          | 50 Hz<br>60 Hz                    |
| Function               | Surface socket outlet for looping |
| Housing Material       | Thermoplastic (PBT)               |

|                            |                                      |
|----------------------------|--------------------------------------|
| Invoice Description        | Ind. P&S#332RL5W                     |
| Mounting Holes             | 171x90                               |
| Number of Poles            | 4                                    |
| Order Multiple             | 1 piece                              |
| Product Main Type          | TRL                                  |
| Product Name               | Industrial Socket Outlet for Looping |
| Protection Type            | Watertight                           |
| Rated Current ( $I_n$ )    | 32 A                                 |
| Rated Voltage ( $U_r$ )    | 600 ... 690 V                        |
| Recommended Screw Driver   | PH2                                  |
| Standards                  | IEC 60309-1, -2                      |
| Suitable For               | Socket Outlets for Looping           |
| Suitable for Product Class | IEC Industrial Plugs and Sockets     |
| Instructions and Manuals   | 2CMC000033M0001                      |
| Installation Manual        | 2CMC000033M0001                      |
| RAL Number                 | RAL 7001 - Silver Grey               |

Classifications

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39120000 |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Looping

