

PRODUCT-DETAILS

432RL3W

Surface socket-outlet for looping, 3h, 32A, IP67, 3P+N+E



General Information

Extended Product Type	432RL3W
Product ID	2CMA168496R1000
EAN	7392696684965
Catalog Description	Surface socket-outlet for looping, 3h, 32A, IP67, 3P+N+E
Long Description	Surface socket-outlet for looping, earthing sleeve position 3h, rated current 32A, IP67 watertight, 3-poles+neutral+earth, frequency 50-60 Hz, color code red

Ordering

E-Number (Sweden)	2417523
E-Number (Finland)	2417523
E-Number (Norway)	2417523
EAN	7392696684965
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	120 mm
Product Net Height	253 mm
Product Net Weight	0.7 kg

Container Information

Package Level 1 Width	152 mm
Package Level 1 Depth / Length	120 mm
Package Level 1 Height	265 mm
Package Level 1 Gross Weight	0.8 kg
Package Level 1 EAN	7392696684965
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	120 kg
Package Level 2 EAN	7392696077170
Package Level 2 Units	pallet (lift) 125 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm²
Cable Diameter	13 ... 21.5 mm
Cable Entry Position	Cable entry, knock-outs 2xØ25mm
Color	Red
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50/60 Hz
Function	Surface socket outlet for looping
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#432RL3W
Mounting Holes	171x90
Number of Poles	5
Order Multiple	1 piece
Product Main Type	TRL
Product Name	Industrial Socket Outlet for Looping
Protection Type	Watertight
Rated Current (I _n)	32 A

Rated Voltage (U _r)	220/380 ... 250/440 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Looping
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000033M0001
Installation Manual	2CMC000033M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Looping

