

PRODUCT-DETAILS

4125RL7W

Surface socket-outlet for looping, 7h, 125A, IP67, 3P+N+E



General Information

Extended Product Type	4125RL7W
Product ID	2CMA168537R1000
EAN	7392696685375
Catalog Description	Surface socket-outlet for looping, 7h, 125A, IP67, 3P+N+E
Long Description	Surface socket-outlet for looping, earthing sleeve position 7h, rated current 125A, IP67 watertight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Black

Ordering

E-Number (Sweden)	2417541
E-Number (Finland)	2417541
E-Number (Norway)	2417541
EAN	7392696685375
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	230 mm
Product Net Height	510 mm
Product Net Weight	4.3 kg

Container Information

Package Level 1 Width	235 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Height	245 mm
Package Level 1 Gross Weight	4.3 kg
Package Level 1 EAN	7392696685375
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	110.3 kg
Package Level 2 EAN	7392696077637
Package Level 2 Units	pallet (lift) 21 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	16 ... 70 mm²
Cable Diameter	24 ... 48 mm
Cable Entry Position	Cable entry, knock-outs 2xØ50/25mm
Color	Black
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Surface socket outlet for looping
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#4125RL7W
Mounting Holes	204,204, 236x204
Number of Poles	5
Order Multiple	1 piece
Product Main Type	TRL
Product Name	Industrial Socket Outlet for Looping
Protection Type	Watertight
Rated Current (I _n)	125 A
	480 ... 500 V

Rated Voltage (U _r)	
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Looping
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000038M0001
Installation Manual	2CMC000038M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Looping

