


PRODUCT-DETAILS

MPR16/3

Modular Combi Plastic, 3x3P+N+E IEC,
3x10/16A Schuko(MCB 203-C16, RCD F204 A-
40/0,03), 250x560x160, IP44



General Information

Extended Product Type	MPR16/3
Product ID	2CMA168995R1000
EAN	7392696689953
Catalog Description	Modular Combi Plastic, 3x3P+N+E IEC, 3x10/16A Schuko(MCB 203-C16, RCD F204 A-40/0,03), 250x560x160, IP44
Long Description	Modular Combi Plastic, 16A, 3x3P+N+E, 3x single Schuko outlets (1P+E) 10/16A (250 V), (3x MCB S201-C16, 2x MCB 203-C16, RCD F204 A-40/0,03), 250x560x160, IP44, Cable entry, 4 knock-outs at the top, 2xØ40mm and 2xØ25mm, Three at the bottom Ø47mm

Ordering

E-Number (Sweden)	E2466347
E-Number (Finland)	3405156
E-Number (Norway)	2466347
EAN	7392696689953
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	250 mm
-------------------	--------

Product Net Height	430 mm
Product Net Weight	5 kg

Container Information

Package Level 1 Width	210 mm
Package Level 1 Depth / Length	270 mm
Package Level 1 Height	490 mm
Package Level 1 Gross Weight	5.32 kg
Package Level 1 EAN	7392696689953
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	977.6 kg
Package Level 2 EAN	7392696077675
Package Level 2 Units	pallet (lift) 180 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0004
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0004
SEMKO Certificate	2CHC660099X0201
REACH Declaration	2CMC700005D0004

Additional Information

Additional Information	Cable entry, 4 knock-outs at the top, 2xØ40mm and 2xØ25mm, Three at the bottom Ø47mm
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	16 mm²
Cable Entry Position	Cable entry, 4 knock-outs at the top, 2xØ40mm and 2xØ25mm, Three at the bottom Ø47mm
Cable Length	0 m
Color	Grey
Connection Type	Screw Clamp
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz

Function	Combination box
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#MPR16/3
Mounting Type	Wall mounting
Number of Poles	5
Number of RCDs 30mA	1
Number of RCDs	1
Number of Schuko Outlets	4
Order Multiple	1 piece
Product Main Type	MPR
Product Name	Modular Combi
Rated Current (I_n)	16 A
Rated Residual Current	30 mA
Rated Voltage (U_r)	346 ... 415 V
Recommended Screw Driver	PH2
Standards	IEC 61439-1 IEC 61439-2
Sub-Function	Cable entry, 4 knock-outs at the top, 2xØ40mm and 2xØ25mm, Three at the bottom Ø47mm
Suitable For	MPR16/3 Modular Combi Plastic
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC711001M0201
Installation Manual	2CMC000026M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440501
UNSPSC	39121406

Technical

Wiring Diagram	9AKK107680A1891
----------------	-----------------

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Modular Combination Boxes

