

PRODUCT-DETAILS

MPR16 Plastic

Modular Combi Plastic, 1x3P+N+E 16A,
2x10/16A Schuko(MCB 203-C16, RCD F204 A-
25/0,03), 250x360x160, IP44



General Information

Extended Product Type	MPR16 Plastic
Product ID	2CMA168997R1000
EAN	7392696689977
Catalog Description	Modular Combi Plastic, 1x3P+N+E 16A, 2x10/16A Schuko(MCB 203-C16, RCD F204 A-25/0,03), 250x360x160, IP44
Long Description	Modular Combi Plastic, 16A, 1x3P+N+E 16A, 2x10/16A (MCB 203-C16, RCD F204 A-25/0,03), IP44, Cable entry, 4 knock-outs at the top, 2xØ40mm and 2xØ25mm, Three at the bottom Ø47mm

Ordering

E-Number (Sweden)	E2466345
E-Number (Finland)	3405154
E-Number (Norway)	2466345
EAN	7392696689977
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	250 mm
-------------------	--------

Product Net Height	300 mm
Product Net Weight	3 kg

Container Information

Package Level 1 Width	210 mm
Package Level 1 Depth / Length	270 mm
Package Level 1 Height	490 mm
Package Level 1 Gross Weight	3.32 kg
Package Level 1 EAN	7392696689977
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	617.6 kg
Package Level 2 EAN	7392696077682
Package Level 2 Units	pallet (lift) 180 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0004
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0004
SEMKO Certificate	2CHC660099X0201
REACH Declaration	2CMC700005D0004

Additional Information

Additional Information	Cable entry, 4 knock-outs at the top, 2xØ40mm and 2xØ25mm, Three at the bottom Ø47mm
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	16 mm²
Cable Entry Position	Cable entry, 4 knock-outs at the top, 2xØ40mm and 2xØ25mm, Three at the bottom Ø47mm
Cable Length	0 m
Color	Grey
Connection Type	Screw Clamp
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz

Function	Combination box
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#MPR16
Mounting Type	Wall mounting
Number of Poles	5
Number of RCDs 30mA	1
Number of RCDs	1
Number of Schuko Outlets	2
Order Multiple	1 piece
Product Main Type	MPR
Product Name	Modular Combi
Rated Current (I_n)	16 A
Rated Residual Current	30 mA
Rated Voltage (U_r)	346 ... 415 V
Recommended Screw Driver	PH2
Standards	IEC 61439-1 IEC 61439-2
Sub-Function	Cable entry, 4 knock-outs at the top, 2xØ40mm and 2xØ25mm, Three at the bottom Ø47mm
Suitable For	MPR16 Modular Combi Plastic
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC711001M0201
Installation Manual	2CMC000026M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440501
UNSPSC	39121406

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Modular Combination Boxes

