

---

PRODUCT-DETAILS

# 316RAM10

## Industrial Socket Outlets Panel Mounting, 3P+E, 16 A, >50 V




---

### General Information

Extended Product Type	316RAM10
Product ID	2CMA170015R1000
EAN	7392696700153
Catalog Description	Industrial Socket Outlets Panel Mounting, 3P+E, 16 A, >50 V
Long Description	Panel mounted socket, earthing sleeve position 10h, rated current 16A, IP44 splashproof, minimized flange, angled, 3-poles+earth, frequency 100-300 Hz, color code Green

---

### Ordering

E-Number (Sweden)	E2416471
E-Number (Finland)	2416471
E-Number (Norway)	2416471
EAN	7392696700153
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

---

### Dimensions

Product Net Width	83 mm
Product Net Height	89 mm

Product Net Weight	0.240 kg
--------------------	----------

---

### Container Information

---

Package Level 1 Width	154 mm
Package Level 1 Depth / Length	182 mm
Package Level 1 Height	378 mm
Package Level 1 Gross Weight	2.4 kg
Package Level 1 EAN	7392696702133
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	1100 kg
Package Level 2 EAN	7392696077804
Package Level 2 Units	pallet (lift) 450 piece

---

### Environmental

---

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

---

### Certificates and Declarations (Document Number)

---

CB Certificate	2CHC660153X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614201
REACH Declaration	2CMC700005D0001

---

### Additional Information

---

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm <sup>2</sup>
Cable Diameter	13 ... 17 mm
Color	Green
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	100 ... 300 Hz
Function	Panel mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#316RAM10

Mounting Holes	66x66
Mounting Type	Minimized angled flange
Number of Poles	4
Order Multiple	10 piece
Product Main Type	ERAM
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current ( $I_n$ )	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage ( $U_r$ )	50 ... 600 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

---

## Classifications

eClass	27440504
UNSPSC	39121406

---

## Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

---

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Socket Outlets for Panel Mounting

