

PRODUCT-DETAILS

CUE 416-6+R/UJP

Surface socket-outlet and 2 pole schuko, 6h,
16A, IP44, 3P+N+E



General Information

Extended Product Type	CUE 416-6+R/UJP
Product ID	2CMA178301R1000
EAN	7392696783019
Catalog Description	Surface socket-outlet and 2 pole schuko, 6h, 16A, IP44, 3P+N+E
Long Description	Wall mounted socket IEC and 2 pole German outlet, earthing sleeve position 6h, rated current 16A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

Ordering

E-Number (Sweden)	E2416014
E-Number (Finland)	2409501
E-Number (Norway)	1562922
EAN	7392696783019
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	82 mm
Product Net Height	112 mm
Product Net Weight	0.32 kg

Container Information

Package Level 1 Width	188 mm
Package Level 1 Depth / Length	175 mm
Package Level 1 Height	428 mm
Package Level 1 Gross Weight	3.2 kg
Package Level 1 EAN	7392696783903
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	172 kg
Package Level 2 EAN	7392696078672
Package Level 2 Units	pallet (lift) 240 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0003
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1618716
REACH Declaration	2CMC700005D0003

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Cable Length	0 m
Color	Red
Connection Type	Screw Clamp
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Wall mounted IEC socket with domestic socket
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#CUE 416-6+R/UJP
Mounting Holes	120x72
Mounting Type	Wall mounting
Number of Poles	5
Order Multiple	10 piece
Product Main Type	CUE
Product Name	Wall mounted IEC socket with domestic socket
Rated Current (I _n)	16 A
	200/346 ... 240/415 V

Rated Voltage (U _r)	
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Sub-Function	Socket outlet with 2 pole schuko 16A
Suitable For	CUE 416-6+R/UJP
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000050M0001
Installation Manual	2CMC000050M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39121406

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Special Plugs & Sockets → Appliances

