

PRODUCT-DETAILS

CUED 416-6+RD

Surface socket-outlet, for surface mounting, 6h,
16A, IP44, 3P+N+E



General Information

Extended Product Type	CUED 416-6+RD
Product ID	2CMA178696R1000
EAN	7392696786966
Catalog Description	Surface socket-outlet, for surface mounting, 6h, 16A, IP44, 3P+N+E
Long Description	Surface socket-outlet, for surface mounting, earthing sleeve position 6h, rated current 16A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

Ordering

E-Number (Sweden)	E2416011
E-Number (Finland)	2416011
E-Number (Norway)	2416011
EAN	7392696786966
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	95 mm
Product Net Height	95 mm
Product Net Weight	0.31 kg

Container Information

Package Level 1 Width	188 mm
Package Level 1 Depth / Length	175 mm
Package Level 1 Height	428 mm
Package Level 1 Gross Weight	3.1 kg
Package Level 1 EAN	7392696385985
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	764 kg
Package Level 2 EAN	7392696078696
Package Level 2 Units	pallet (lift) 240 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0003
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614205
REACH Declaration	2CMC700005D0003

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Cable Entry Position	Cable entries, four alternative knock-out entries Ø.5, Ø23, Ø25.5 and Ø29mm
Color	Colour: Grey Identification colour: Red
Configuration Type	Closed cover
Connection Type	Screw Clamp
Degree of Protection	IP44
Design	Wall mounted socket
Frequency (f)	50 Hz 60 Hz
Function	Socket outlet for surface mounting
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#CUED 416-6+RD
Mounting Holes	53x53
Mounting Type	minimized flange, straight
Number of Poles	5
Order Multiple	10 piece
Product Main Type	CUED

Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current (I _n)	16 A
Rated Voltage (U _r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Sub-Function	Cable entries, four alternative knock-out entries Ø 5, Ø 23, Ø 25.5 and Ø 29mm
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7035 - Light Grey

Classifications

eClass	27440510
UNSPSC	39121406

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Socket Outlets for Panel Mounting

