


PRODUCT-DETAILS

316RS4

Surface socket-outlet, 4h, 16A, IP44, 3P+E



General Information

Extended Product Type	316RS4
Product ID	2CMA193104R1000
EAN	7392696931045
Catalog Description	Surface socket-outlet, 4h, 16A, IP44, 3P+E
Long Description	Wall mounted socket, earthing sleeve position 4h, rated current 16A, IP44 splashproof, 3-poles+earth, frequency 50-60 Hz, color code Yellow

Ordering

E-Number (Sweden)	E2416447
E-Number (Finland)	2420181
E-Number (Norway)	1542311
EAN	7392696931045
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	79 mm
Product Net Height	79 mm
Product Net Weight	0.24 kg
Mechanical Drawings	9AKK107680A0701

Container Information

Package Level 1 Width	154 mm
Package Level 1 Depth / Length	182 mm
Package Level 1 Height	378 mm
Package Level 1 Gross Weight	2.4 kg
Package Level 1 EAN	7392696661041
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	1100 kg
Package Level 2 EAN	7392696079112
Package Level 2 Units	pallet (lift) 450 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm ²
Cable Diameter	18 mm
Cable Entry Position	Cable entry, flexible membrane and metric threaded M20 insert for top cable entry.Rear knock-out cable entry.
Color	Yellow
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Wall mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#316RS4
Mounting Holes	91x67
Mounting Type	Angled
Number of Poles	4
Order Multiple	10 piece
Product Main Type	ERS

Product Name	Wall mounted socket
Protection Type	Splashproof
Rated Current (I_n)	16 A
Rated Voltage (U_r)	100 ... 130 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Surface Socket Outlets
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
Installation Manual	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440510
UNSPSC	39121406

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Socket Outlets

