

PRODUCT-DETAILS

# 316RS9

## Surface socket-outlet, 9h, 16A, IP44, 3P+E



### General Information

Extended Product Type	316RS9
Product ID	2CMA193108R1000
EAN	7392696931083
Catalog Description	Surface socket-outlet, 9h, 16A, IP44, 3P+E
Long Description	Wall mounted socket, earthing sleeve position 9h, rated current 16A, IP44 splashproof, 3-poles+earth, frequency 50-60 Hz, color code Blue

### Ordering

E-Number (Sweden)	E2416451
E-Number (Finland)	2416451
E-Number (Norway)	2416451
EAN	7392696931083
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

### Dimensions

Product Net Width	79 mm
Product Net Height	79 mm

Product Net Weight	0.24 kg
Mechanical Drawings	9AKK107680A0701

## Container Information

Package Level 1 Width	154 mm
Package Level 1 Depth / Length	182 mm
Package Level 1 Height	378 mm
Package Level 1 Gross Weight	2.4 kg
Package Level 1 EAN	7392696661089
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	1100 kg
Package Level 2 EAN	7392696079150
Package Level 2 Units	pallet (lift) 450 piece

## Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

## Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm <sup>2</sup>
Cable Diameter	18 mm
Cable Entry Position	Cable entry, flexible membrane and metric threaded M20 insert for top cable entry.Rear knock-out cable entry.
Color	Blue
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Wall mounted socket

Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#316RS9
Mounting Holes	91x67
Mounting Type	Angled
Number of Poles	4
Order Multiple	10 piece
Product Main Type	ERS
Product Name	Wall mounted socket
Protection Type	Splashproof
Rated Current ( $I_n$ )	16 A
Rated Voltage ( $U_r$ )	200 ... 250 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Surface Socket Outlets
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
Installation Manual	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

## Classifications

eClass	27440510
UNSPSC	39120000

## Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Socket Outlets

