
PRODUCT-DETAILS

316R1

Industrial Socket Outlets Panel Mounting, 3P+E, 16 A, Optional voltage V



General Information

| | |
|-----------------------|--|
| Extended Product Type | 316R1 |
| Product ID | 2CMA193159R1000 |
| EAN | 7392696931595 |
| Catalog Description | Industrial Socket Outlets Panel Mounting, 3P+E, 16 A, Optional voltage V |
| Long Description | Panel mounted socket, earthing sleeve position 1h, rated current 16A, IP44 splashproof, 3-poles+neutral+earth, frequency AC, color code Grey |

Ordering

| | |
|------------------------|---------------------|
| E-Number (Sweden) | 2416614 |
| E-Number (Finland) | 2416614 |
| E-Number (Norway) | 2416614 |
| EAN | 7392696931595 |
| Country of Origin | Czech Republic (CZ) |
| Minimum Order Quantity | 10 piece |

Dimensions

| | |
|--------------------|-------|
| Product Net Width | 66 mm |
| Product Net Height | 87 mm |

| | |
|--------------------|----------|
| Product Net Weight | 0.250 kg |
|--------------------|----------|

Container Information

| | |
|--------------------------------|-------------------------|
| Package Level 1 Width | 138 mm |
| Package Level 1 Depth / Length | 158 mm |
| Package Level 1 Height | 345 mm |
| Package Level 1 Gross Weight | 2.5 kg |
| Package Level 1 EAN | 7392696661591 |
| Package Level 1 Units | box 10 piece |
| Package Level 2 Width | 800 mm |
| Package Level 2 Depth / Length | 1200 mm |
| Package Level 2 Height | 900 mm |
| Package Level 2 Gross Weight | 1670 kg |
| Package Level 2 EAN | 7392696079884 |
| Package Level 2 Units | pallet (lift) 660 piece |

Environmental

| | |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information | 2CMC000056M0000 |
| RoHS Information | 2CMC700005D0001 |
| SEMKO Certificate | 1613211 |
| REACH Declaration | 2CMC700005D0001 |

Additional Information

| | |
|------------------------|---------------------------|
| Additional Information | 3P+E |
| Ambient Temperature | -25 ... 40 °C |
| Cable Cross-Section | 1.5 ... 4 mm ² |
| Cable Diameter | 13 ... 17 mm |
| Color | Grey |
| Connection Type | Screw |
| Degree of Protection | IP44 |
| Frequency (f) | AC Hz |
| Function | Panel mounted socket |
| Housing Material | Plastic (PA) |
| Invoice Description | Ind. P&S#316R1 |
| Mounting Holes | 51x51 |

| | |
|----------------------------|----------------------------------|
| Mounting Type | Minimized straight flange |
| Number of Poles | 4 |
| Order Multiple | 10 piece |
| Product Main Type | ER |
| Product Name | Panel mounted socket |
| Protection Type | Splashproof |
| Rated Current (I_n) | 16 A |
| Rated Frequency (f) | 50...60 Hz |
| Rated Voltage (U_r) | Optional voltage V |
| Recommended Screw Driver | PH2 |
| Standards | IEC 60309-1, -2 |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals | 2CMC700014C0016 |
| RAL Number | RAL 7001 - Silver Grey |

Classifications

| | |
|--------|----------|
| eClass | 27440504 |
| UNSPSC | 39121406 |

Technical

| | |
|-------------------|------------------|
| Wire Size | 14 ... 12 AWG |
| Tightening Torque | WireClamp0.8 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Socket Outlets

