

## PRODUCT-DETAILS

# 216RU12

## Industrial socket outlets for panel mounting, 2P+E, 16 A, Isol. Transformer V



### General Information

|                       |                                                                                                                                                                       |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 216RU12                                                                                                                                                               |
| Product ID            | 2CMA193172R1000                                                                                                                                                       |
| EAN                   | 7392696931724                                                                                                                                                         |
| Catalog Description   | Industrial socket outlets for panel mounting, 2P+E, 16 A, Isol. Transformer V                                                                                         |
| Long Description      | Panel mounted socket, earthing sleeve position 12h, rated current 16A, IP44 splashproof, unified flange, straight, 2-poles+earth, frequency 50-60 Hz, color code Grey |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2416622            |
| E-Number (Finland)     | 2416622             |
| E-Number (Norway)      | 2416622             |
| EAN                    | 7392696931724       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 10 piece            |

### Dimensions

|                    |          |
|--------------------|----------|
| Product Net Width  | 75 mm    |
| Product Net Height | 79 mm    |
| Product Net Weight | 0.200 kg |

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 138 mm                  |
| Package Level 1 Depth / Length | 158 mm                  |
| Package Level 1 Height         | 345 mm                  |
| Package Level 1 Gross Weight   | 2 kg                    |
| Package Level 1 EAN            | 7392696661720           |
| Package Level 1 Units          | box 10 piece            |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 1340 kg                 |
| Package Level 2 EAN            | 7392696079402           |
| Package Level 2 Units          | pallet (lift) 660 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1613211         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                                 |                         |
|---------------------------------|-------------------------|
| Additional Information          | 2P+E                    |
| Ambient Temperature             | -25 ... 40 °C           |
| Cable Cross-Section             | 1.5 ... 4 mm²           |
| Cable Diameter                  | 6 ... 13 mm             |
| Color                           | Grey                    |
| Connection Type                 | Screw                   |
| Degree of Protection            | IP44                    |
| Frequency (f)                   | 50 Hz<br>60 Hz          |
| Function                        | Panel mounted socket    |
| Housing Material                | Plastic (PA)            |
| Invoice Description             | Ind. P&S#216RU12        |
| Mounting Holes                  | 60-61x60-61             |
| Mounting Type                   | Unified straight flange |
| Number of Poles                 | 3                       |
| Order Multiple                  | 10 piece                |
| Product Main Type               | ERU                     |
| Product Name                    | Panel mounted socket    |
| Protection Type                 | Splashproof             |
| Rated Current (I <sub>n</sub> ) | 16 A                    |

|                                 |                                  |
|---------------------------------|----------------------------------|
| Rated Frequency (f)             | 50...60 Hz                       |
| Rated Voltage (U <sub>r</sub> ) | Isol. Transformer V              |
| Recommended Screw Driver        | PH2                              |
| Standards                       | IEC 60309-1, -2                  |
| Suitable for Product Class      | IEC Industrial Plugs and Sockets |
| Instructions and Manuals        | 2CMC700014C0016                  |
| RAL Number                      | RAL 7001 - Silver Grey           |

Classifications

|        |          |
|--------|----------|
| eClass | 27440504 |
| UNSPSC | 39121406 |

Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 14 ... 12 AWG    |
| Tightening Torque | WireClamp0.8 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Socket Outlets for Panel Mounting

