

---

PRODUCT-DETAILS

## 216RAU9

### Industrial Socket Outlets Panel Mounting, 2P+E, 16 A, 380 ... 415 V




---

#### General Information

Extended Product Type	216RAU9
Product ID	2CMA193219R1000
EAN	7392696932196
Catalog Description	Industrial Socket Outlets Panel Mounting, 2P+E, 16 A, 380 ... 415 V
Long Description	Panel mounted socket, earthing sleeve position 9h, rated current 16A, IP44 splashproof, unified flange, angled, 2-poles+earth, frequency 50-60 Hz, color code Red

---

#### Ordering

E-Number (Sweden)	2416638
E-Number (Finland)	2421951
E-Number (Norway)	2416638
EAN	7392696932196
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

---

#### Dimensions

Product Net Width	110 mm
Product Net Height	96 mm

Product Net Weight	0.24 kg
--------------------	---------

---

### Container Information

---

Package Level 1 Width	154 mm
Package Level 1 Depth / Length	182 mm
Package Level 1 Height	378 mm
Package Level 1 Gross Weight	2.4 kg
Package Level 1 EAN	7392696662192
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	1100 kg
Package Level 2 EAN	7392696079570
Package Level 2 Units	pallet (lift) 450 piece

---

### Environmental

---

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

---

### Certificates and Declarations (Document Number)

---

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

---

### Additional Information

---

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm <sup>2</sup>
Cable Diameter	6 ... 13 mm
Color	Red
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Panel mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#216RAU9

Mounting Holes	85x85
Mounting Type	Unified angled flange
Number of Poles	3
Order Multiple	10 piece
Product Main Type	ERAU
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current ( $I_n$ )	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage ( $U_r$ )	380 ... 415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC00058M0001
Installation Manual	2CMC00058M0001
RAL Number	RAL 7001 - Silver Grey

## Classifications

eClass	27440504
UNSPSC	39121406

## Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Socket Outlets for Panel Mounting

