

PRODUCT-DETAILS

332RAU5

Socket-outlet, panel mounting, 5h, 32A, IP44, unified flange, angled, 3P+E



General Information

| | |
|-----------------------|---|
| Extended Product Type | 332RAU5 |
| Product ID | 2CMA193273R1000 |
| EAN | 7392696932738 |
| Catalog Description | Socket-outlet, panel mounting, 5h, 32A, IP44, unified flange, angled, 3P+E |
| Long Description | Panel mounted socket, earthing sleeve position 5h, rated current 32A, IP44 splashproof, unified flange, angled, 3-poles+earth, frequency 50-60 Hz, color code Black |

Ordering

| | |
|------------------------|---------------------|
| E-Number (Sweden) | 2416665 |
| E-Number (Finland) | 2409550 |
| E-Number (Norway) | 1547449 |
| EAN | 7392696932738 |
| Country of Origin | Czech Republic (CZ) |
| Minimum Order Quantity | 10 piece |

Dimensions

| | |
|--------------------|---------|
| Product Net Width | 110 mm |
| Product Net Height | 110 mm |
| Product Net Weight | 0.26 kg |

Container Information

| | |
|--------------------------------|-------------------------|
| Package Level 1 Width | 188 mm |
| Package Level 1 Depth / Length | 175 mm |
| Package Level 1 Height | 428 mm |
| Package Level 1 Gross Weight | 2.6 kg |
| Package Level 1 EAN | 7392696662734 |
| Package Level 1 Units | box 10 piece |
| Package Level 2 Width | 800 mm |
| Package Level 2 Depth / Length | 1200 mm |
| Package Level 2 Height | 900 mm |
| Package Level 2 Gross Weight | 644 kg |
| Package Level 2 EAN | 7392696080125 |
| Package Level 2 Units | pallet (lift) 240 piece |

Environmental

| | |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information | 2CMC000056M0000 |
| RoHS Information | 2CMC700005D0001 |
| SEMKO Certificate | 1613211 |
| REACH Declaration | 2CMC700005D0001 |

Additional Information

| | |
|---------------------------------|----------------------------|
| Additional Information | 3P+E |
| Ambient Temperature | -25 ... 40 °C |
| Cable Cross-Section | 2.5 ... 10 mm ² |
| Cable Diameter | 13 ... 21.5 mm |
| Color | Black |
| Connection Type | Screw |
| Degree of Protection | IP44 |
| Frequency (f) | 50 Hz 60 Hz |
| Function | Panel mounted socket |
| Housing Material | Plastic (PA) |
| Invoice Description | Ind. P&S#332RAU5 |
| Mounting Holes | 85x85 |
| Mounting Type | Unified angled flange |
| Number of Poles | 4 |
| Order Multiple | 10 piece |
| Product Main Type | ERAU |
| Product Name | Panel mounted socket |
| Protection Type | Splashproof |
| Rated Current (I _n) | 32 A |

| | |
|---------------------------------|----------------------------------|
| Rated Frequency (f) | 50...60 Hz |
| Rated Voltage (U _r) | 600 ... 690 V |
| Recommended Screw Driver | PH2 |
| Standards | IEC 60309-1, -2 |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals | 2CMC00058M0001 |
| Installation Manual | 2CMC00058M0001 |
| RAL Number | RAL 7001 - Silver Grey |

Classifications

| | |
|--------|----------|
| eClass | 27440504 |
| UNSPSC | 39121406 |

Technical

| | |
|-------------------|------------------|
| Wire Size | 12 ... 10 AWG |
| Tightening Torque | WireClamp1.2 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Socket Outlets for Panel Mounting

