


## PRODUCT-DETAILS

# 316BS9

## Surface inlet, 9h, 16A, IP44, 3P+E



### General Information

|                       |                                                                                                                                          |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 316BS9                                                                                                                                   |
| Product ID            | 2CMA193300R1000                                                                                                                          |
| EAN                   | 7392696933001                                                                                                                            |
| Catalog Description   | Surface inlet, 9h, 16A, IP44, 3P+E                                                                                                       |
| Long Description      | Wall mounted inlet, earthing sleeve position 9h, rated current 16A, IP44 splashproof, 3-poles+earth, frequency 50-60 Hz, color code Blue |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2417170            |
| E-Number (Finland)     | 2417170             |
| E-Number (Norway)      | 2417170             |
| EAN                    | 7392696933001       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 10 piece            |

### Dimensions

|                     |                 |
|---------------------|-----------------|
| Product Net Width   | 78 mm           |
| Product Net Height  | 68 mm           |
| Product Net Weight  | 0.19 kg         |
| Mechanical Drawings | 9AKK107680A3025 |

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 154 mm                  |
| Package Level 1 Depth / Length | 182 mm                  |
| Package Level 1 Height         | 378 mm                  |
| Package Level 1 Gross Weight   | 1.9 kg                  |
| Package Level 1 EAN            | 7392696663007           |
| Package Level 1 Units          | box 10 piece            |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 875 kg                  |
| Package Level 2 EAN            | 7392696080286           |
| Package Level 2 Units          | pallet (lift) 450 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 2CHC660161X0201 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                           |
|------------------------|---------------------------|
| Additional Information | 3P+E                      |
| Ambient Temperature    | -25 ... 40 °C             |
| Cable Cross-Section    | 1.5 ... 4 mm <sup>2</sup> |
| Cable Diameter         | 18 mm                     |
| Color                  | Blue                      |
| Connection Type        | Screw                     |
| Degree of Protection   | IP44                      |
| Design                 | Surface mounted plug      |
| Frequency (f)          | 50 Hz<br>60 Hz            |
| Function               | Wall mounted inlet        |
| Housing Material       | Plastic (PA)              |
| Invoice Description    | Ind. P&S#316BS9           |
| Mounting Holes         | 111x72                    |
| Mounting Type          | Angled                    |
| Number of Poles        | 4                         |
| Order Multiple         | 10 piece                  |
| Product Main Type      | EBS                       |
| Product Name           | Wall mounted inlet        |

|                                 |                                  |
|---------------------------------|----------------------------------|
| Protection Type                 | Splashproof                      |
| Rated Current (I <sub>n</sub> ) | 16 A                             |
| Rated Frequency (f)             | 50...60 Hz                       |
| Rated Voltage (U <sub>r</sub> ) | 200 ... 250 V                    |
| Recommended Screw Driver        | PH2                              |
| Standards                       | IEC 60309-1, -2                  |
| Suitable For                    | Surface Inlets                   |
| Suitable for Product Class      | IEC Industrial Plugs and Sockets |
| Instructions and Manuals        | 2CMC700014C0016                  |
| RAL Number                      | RAL 7012 - Basalt Grey           |

Classifications

|        |          |
|--------|----------|
| eClass | 27440519 |
| UNSPSC | 39121406 |

Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 14 ... 12 AWG    |
| Tightening Torque | WireClamp0.8 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Inlets

