

PRODUCT-DETAILS

316BS10

Industrial Inlets, 3P+E, 16 A, >50 V



General Information

Extended Product Type	316BS10
Product ID	2CMA193301R1000
EAN	7392696933018
Catalog Description	Industrial Inlets, 3P+E, 16 A, >50 V
Long Description	Wall mounted inlet, earthing sleeve position 10h, rated current 16A, IP44 splashproof, 3-poles+earth, frequency 100-300 Hz, color code green

Ordering

E-Number (Sweden)	2417171
E-Number (Finland)	2417171
E-Number (Norway)	2417171
EAN	7392696933018
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	78 mm
Product Net Height	68 mm
Product Net Weight	0.190 kg
Mechanical Drawings	9AKK107680A3025

Container Information

Package Level 1 Width	154 mm
Package Level 1 Depth / Length	182 mm
Package Level 1 Height	378 mm
Package Level 1 Gross Weight	1.9 kg
Package Level 1 EAN	7392696663014
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	875 kg
Package Level 2 EAN	7392696080293
Package Level 2 Units	pallet (lift) 450 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	2CHC660161X0201
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm ²
Cable Diameter	18 mm
Color	Green
Connection Type	Screw
Degree of Protection	IP44
Design	Surface mounted plug
Frequency (f)	100 ... 300 Hz
Function	Wall mounted inlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#316BS10
Mounting Holes	111x72
Mounting Type	Angled
Number of Poles	4
Order Multiple	10 piece
Product Main Type	EBS
Product Name	Wall mounted inlet

Protection Type	Splashproof
Rated Current (I _n)	16 A
Rated Frequency (f)	100...300 Hz
Rated Voltage (U _r)	50 ... 600 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440519
UNSPSC	39121406

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Inlets

