

## PRODUCT-DETAILS

# 232BS6

## Surface inlet, 6h, 32A, IP44, 2P+E



### General Information

|                       |                                                                                                                                          |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 232BS6                                                                                                                                   |
| Product ID            | 2CMA193314R1000                                                                                                                          |
| EAN                   | 7392696933148                                                                                                                            |
| Catalog Description   | Surface inlet, 6h, 32A, IP44, 2P+E                                                                                                       |
| Long Description      | Wall mounted inlet, earthing sleeve position 6h, rated current 32A, IP44 splashproof, 2-poles+earth, frequency 50-60 Hz, color code Blue |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2417180            |
| E-Number (Finland)     | 2421522             |
| E-Number (Norway)      | 1542402             |
| EAN                    | 7392696933148       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 10 piece            |

### Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 79 mm  |
| Product Net Height | 104 mm |

|                     |                 |
|---------------------|-----------------|
| Product Net Weight  | 0.44 kg         |
| Mechanical Drawings | 9AKK107680A3027 |

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 188 mm                  |
| Package Level 1 Depth / Length | 175 mm                  |
| Package Level 1 Height         | 428 mm                  |
| Package Level 1 Gross Weight   | 4.4 kg                  |
| Package Level 1 EAN            | 7392696663144           |
| Package Level 1 Units          | box 10 piece            |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 1076 kg                 |
| Package Level 2 EAN            | 7392696080385           |
| Package Level 2 Units          | pallet (lift) 240 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 2CHC660162X0201 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                      |
|------------------------|----------------------|
| Additional Information | 2P+E                 |
| Ambient Temperature    | -25 ... 40 °C        |
| Cable Cross-Section    | 2.5 ... 10 mm²       |
| Cable Diameter         | 22 mm                |
| Color                  | Blue                 |
| Connection Type        | Screw                |
| Degree of Protection   | IP44                 |
| Design                 | Surface mounted plug |
| Frequency (f)          | 50 Hz<br>60 Hz       |
| Function               | Wall mounted inlet   |

|                            |                                  |
|----------------------------|----------------------------------|
| Housing Material           | Plastic (PA)                     |
| Invoice Description        | Ind. P&S#232BS6                  |
| Mounting Holes             | 111x72                           |
| Mounting Type              | Angled                           |
| Number of Poles            | 3                                |
| Order Multiple             | 10 piece                         |
| Product Main Type          | EBS                              |
| Product Name               | Wall mounted inlet               |
| Protection Type            | Splashproof                      |
| Rated Current ( $I_n$ )    | 32 A                             |
| Rated Frequency (f)        | 50...60 Hz                       |
| Rated Voltage ( $U_r$ )    | 200 ... 250 V                    |
| Recommended Screw Driver   | PH2                              |
| Standards                  | IEC 60309-1, -2                  |
| Suitable For               | Surface Inlets                   |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC700014C0016                  |
| RAL Number                 | RAL 7012 - Basalt Grey           |

---

## Classifications

|        |          |
|--------|----------|
| eClass | 27440519 |
| UNSPSC | 39121406 |

---

## Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 12 ... 10 AWG    |
| Tightening Torque | WireClamp1.2 N·m |

---

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Inlets

