

PRODUCT-DETAILS

216B1

Inlet Panel Mounting, minimized flange, straight, earthing sleeve position 1h, rated current 16A, IP44 splashproof, 2-poles+earth, frequency ACz, color code Grey



General Information

Extended Product Type	216B1
Product ID	2CMA193341R1000
EAN	7392696933414
Catalog Description	Inlet Panel Mounting, minimized flange, straight, earthing sleeve position 1h, rated current 16A, IP44 splashproof, 2-poles+earth, frequency ACz, color code Grey
Long Description	Panel mounted inlet, minimized flange, straight, earthing sleeve position 1h, rated current 16A, IP44 splashproof, 2-poles+earth, frequency ACz, color code Grey Clock Position Of Grounding Contact 1 hour Color code Grey

Ordering

E-Number (Sweden)	2417332
E-Number (Finland)	2417332
E-Number (Norway)	2417332
EAN	7392696933414
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	56 mm
-------------------	-------

Product Net Height	60 mm
Product Net Weight	0.100 kg

Container Information

Package Level 1 Width	120 mm
Package Level 1 Depth / Length	138 mm
Package Level 1 Height	285 mm
Package Level 1 Gross Weight	1 kg
Package Level 1 EAN	7392696663410
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	1220 kg
Package Level 2 EAN	7392696080552
Package Level 2 Units	pallet (lift) 1200 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	2CHC660161X0201
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Cable Diameter	6 ... 13 mm
Color	Grey
Connection Type	Screw
Degree of Protection	IP44
Design	Surface mounted plug
Frequency (f)	AC Hz
Function	Panel mounted inlet
Housing Material	Plastic (PA)

Invoice Description	Ind. P&S#216B1
Mounting Holes	45x45
Mounting Type	Minimized straight flange
Number of Poles	3
Order Multiple	10 piece
Product Main Type	EB
Product Name	Panel mounted inlet
Protection Type	Splashproof
Rated Current (I_n)	16 A
Rated Voltage (U_r)	Optional voltage V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440519
UNSPSC	39121406

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Inlets for Panel Mounting

