

PRODUCT-DETAILS

232BU1

Panel mounted inlet, 2P+E, 32 A, Optional voltage V



General Information

Extended Product Type	232BU1
Product ID	2CMA193437R1000
EAN	7392696934374
Catalog Description	Panel mounted inlet, 2P+E, 32 A, Optional voltage V
Long Description	Panel mounted inlet, earthing sleeve position 1h, rated current 32A, IP44 splashproof, unified flange, straight, 2-poles+earth, frequency AC, color code Grey

Ordering

E-Number (Sweden)	2417342
E-Number (Finland)	2417342
E-Number (Norway)	2417342
EAN	7392696934374
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	75 mm
Product Net Height	75 mm

Product Net Weight	0.150 kg
--------------------	----------

Container Information

Package Level 1 Width	138 mm
Package Level 1 Depth / Length	158 mm
Package Level 1 Height	345 mm
Package Level 1 Gross Weight	1.5 kg
Package Level 1 EAN	7392696664370
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	1010 kg
Package Level 2 EAN	7392696080644
Package Level 2 Units	pallet (lift) 660 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	2CHC660162X0201
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm ²
Cable Diameter	13 ... 21.5 mm
Color	Grey
Connection Type	Screw
Degree of Protection	IP44
Design	Surface mounted plug
Frequency (f)	AC Hz
Function	Panel mounted inlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#232BU1

Mounting Holes	60x66
Mounting Type	Unified straight flange
Number of Poles	3
Order Multiple	10 piece
Product Main Type	EBU
Product Name	Panel mounted inlet
Protection Type	Splashproof
Rated Current (I_n)	32 A
Rated Voltage (U_r)	Optional voltage V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440519
UNSPSC	39121406

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Inlets for Panel Mounting

