

## PRODUCT-DETAILS

# 332BU6

Inlet, panel mounting, 6h, 32A, IP44, unified flange, straight, 3P+E



## General Information

|                       |                                                                                                                                                                    |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 332BU6                                                                                                                                                             |
| Product ID            | 2CMA193442R1000                                                                                                                                                    |
| EAN                   | 7392696934428                                                                                                                                                      |
| Catalog Description   | Inlet, panel mounting, 6h, 32A, IP44, unified flange, straight, 3P+E                                                                                               |
| Long Description      | Panel mounted inlet, earthing sleeve position 6h, rated current 32A, IP44 splashproof, unified flange, straight, 3-poles+earth, frequency 50-60 Hz, color code Red |

## Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2417344            |
| E-Number (Finland)     | 2421543             |
| E-Number (Norway)      | 1544043             |
| EAN                    | 7392696934428       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 10 piece            |

## Dimensions

|                    |       |
|--------------------|-------|
| Product Net Width  | 75 mm |
| Product Net Height | 75 mm |

|                    |         |
|--------------------|---------|
| Product Net Weight | 0.17 kg |
|--------------------|---------|

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 138 mm                  |
| Package Level 1 Depth / Length | 158 mm                  |
| Package Level 1 Height         | 345 mm                  |
| Package Level 1 Gross Weight   | 1.7 kg                  |
| Package Level 1 EAN            | 7392696664424           |
| Package Level 1 Units          | box 10 piece            |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 1142 kg                 |
| Package Level 2 EAN            | 7392696080668           |
| Package Level 2 Units          | pallet (lift) 660 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 2CHC660162X0201 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                            |
|------------------------|----------------------------|
| Additional Information | 3P+E                       |
| Ambient Temperature    | -25 ... 40 °C              |
| Cable Cross-Section    | 2.5 ... 10 mm <sup>2</sup> |
| Cable Diameter         | 13 ... 21.5 mm             |
| Color                  | Red                        |
| Connection Type        | Screw                      |
| Degree of Protection   | IP44                       |
| Design                 | Surface mounted plug       |
| Frequency (f)          | 50 Hz<br>60 Hz             |
| Function               | Panel mounted inlet        |
| Housing Material       | Plastic (PA)               |

|                                 |                                  |
|---------------------------------|----------------------------------|
| Invoice Description             | Ind. P&S#332BU6                  |
| Mounting Holes                  | 60x66                            |
| Mounting Type                   | Unified straight flange          |
| Number of Poles                 | 4                                |
| Order Multiple                  | 10 piece                         |
| Product Main Type               | EBU                              |
| Product Name                    | Panel mounted inlet              |
| Protection Type                 | Splashproof                      |
| Rated Current (I <sub>n</sub> ) | 32 A                             |
| Rated Frequency (f)             | 50...60 Hz                       |
| Rated Voltage (U <sub>r</sub> ) | 380 ... 415 V                    |
| Recommended Screw Driver        | PH2                              |
| Standards                       | IEC 60309-1, -2                  |
| Suitable For                    | Inlets for Panel Mounting        |
| Suitable for Product Class      | IEC Industrial Plugs and Sockets |
| Instructions and Manuals        | 2CMC700014C0016                  |
| RAL Number                      | RAL 7001 - Silver Grey           |

Classifications

|        |          |
|--------|----------|
| eClass | 27440519 |
| UNSPSC | 39121406 |

Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 12 ... 10 AWG    |
| Tightening Torque | WireClamp1.2 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Inlets for Panel Mounting

