

PRODUCT-DETAILS

TL405S

TL405S TL wall moun. PCII IP55



General Information

Extended Product Type	TL405S
Product ID	2CPX010113R9999
EAN	4011617101130
Catalog Description	TL405S TL wall moun. PCII IP55

Long Description	Wall-mounting cabinet, series TwinLine, empty cabinet, for the internal use, with Door, class of protection II (double insulated), degree of protection IP55, applicable standards: EN 61439-1, EN 61439-2, EN 61439-3, IK code 08, powder-coated, in RAL 7035, enclosure out of sheet steel, double door, door out of sheet steel, with Standard locking mechanism double bit, door opening angle 180 degree, door hinge right and left, rear wall out of sheet steel, cable entry on top via flange opening pre-cut, on bottom via flange opening pre-punched, on side via flange opening pre-punched, dimensions in mm (H x W x D): 800 x 1050 x 275, Grid unit 5 GU, Overall height 1, panel width 4, Space units 240, pre-assembled for installation of metering-, modules, Combi-Sets, CombiLine-Modul or mounting plate on EDF-/WR-mounting frame
------------------	---

Ordering

EAN	4011617101130
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000

Dimensions

Product Net Width	1050 mm
Product Net Height	800 mm
Product Net Depth / Length	275 mm
Product Net Weight	36.451 kg

Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	1110.000 mm
Package Level 1 Height	810.000 mm
Package Level 1 Depth / Length	325.000 mm
Package Level 1 Gross Weight	37.912 kg
Package Level 1 EAN	4011617101130
Package Level 2 Units	pallet (lift) 2 piece
Package Level 2 Width	800.000 mm
Package Level 2 Height	984.000 mm
Package Level 2 Depth / Length	1200.000 mm
Package Level 2 Gross Weight	92.908 kg

Additional Information

Color	light grey
Configuration Type	pre-assembled for installation of metering-, modules, CombiLine-Modul or mounting plate on EDF-/WR-mounting frame
Cover Plate Type	None
Degree of Protection	IP55
DIN Place Units	240
Enclosure Type	Wall-mounting cabinet
Enclosure Type of Height	1
Field Width	4
Housing Material	Steel plate/plastic
Interior Depth	222.5 mm
Mounting Type	Surface-mounted
Number of Rows	5
Power Loss	$\Delta t = 20K$ 108.9 W $\Delta t = 25K$ 143.7 W $\Delta t = 30K$ 180.3 W
Product Main Type	TL
Product Name	TL405S TL wall moun. PCII IP55
Protection Class	Isolated
Standards	DIN EN 61439-3 DIN EN 61439-2
Surface Finishing	Powder coating

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	2CPC000001C0101
	2CPC000002C0101
Declaration of Conformity - CE	No declaration needed
Environmental Information	2CPC100001X0201
Instructions and Manuals	2CPC119660M5601
	2CPC016708M5601

Classifications	
ETIM 4	EC000058 - Empty cabinet
ETIM 5	EC000058 - Empty cabinet
ETIM 6	EC000058 - Empty cabinet
ETIM 7	EC000058 - Empty cabinet
Object Classification Code	U
WEEE Category	Product Not in WEEE Scope

Categories
Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Sub Distribution Boards → TwinLine N 55 - Welded

