

PRODUCT-DETAILS

TL409SB

TL409SB TL wall moun. PCII IP30 Basic



General Information

Extended Product Type	TL409SB
Product ID	2CPX010354R9999
EAN	4011617103547
Catalog Description	TL409SB TL wall moun. PCII IP30 Basic
Long Description	Wall-mounting cabinet, series TwinLine, empty cabinet, for the internal use, without door, class of protection II (double insulated), degree of protection IP30, applicable standards: EN 61439-1, EN 61439-2, EN 61439-3, IK code 08, powder-coated, in RAL 7035, enclosure out of sheet steel, without door, rear wall out of sheet steel, cable entry on top via flange opening pre-cut, on bottom via flange opening pre-punched, on side via flange opening pre-punched, dimensions in mm (H x W x D): 1400 x 1050 x 275, Grid unit 9 GU, Overall height 5, panel width 4, Space units 432, pre-assembled for installation of metering-, modules, Combi-Sets, CombiLine-Modul or mounting plate on EDF-/WR-mounting frame

Ordering

EAN	4011617103547
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000

Dimensions

Product Net Width	1050 mm
-------------------	---------

Product Net Height	1400 mm
Product Net Depth / Length	275 mm
Product Net Weight	31.539 kg

Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	1110.000 mm
Package Level 1 Height	1410.000 mm
Package Level 1 Depth / Length	325.000 mm
Package Level 1 Gross Weight	32.816 kg
Package Level 1 EAN	4011617103547
Package Level 2 Units	pallet (lift) 2 piece
Package Level 2 Width	800.000 mm
Package Level 2 Height	1584.000 mm
Package Level 2 Depth / Length	1200.000 mm
Package Level 2 Gross Weight	83.108 kg

Additional Information

Color	light grey
Configuration Type	pre-assembled for installation of metering-, modules, CombiLine-Modul or mounting plate on EDF-/WR-mounting frame
Cover Plate Type	None
Degree of Protection	IP30
DIN Place Units	432
Enclosure Type	Wall-mounting cabinet
Enclosure Type of Height	5
Field Width	4
Housing Material	Steel plate/plastic
Interior Depth	222.5 mm
Mounting Type	Surface-mounted
Number of Rows	9
Power Loss	$\Delta t = 20K$ 179.1 W $\Delta t = 25K$ 236.3 W $\Delta t = 30K$ 296.5 W
Product Main Type	TL
Product Name	TL409SB TL wall moun. PCII IP30 Basic
Protection Class	Isolated
Standards	DIN EN 61439-3 DIN EN 61439-2
Surface Finishing	Powder coating

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	2CPC000001C0101 2CPC000002C0101
Declaration of Conformity - CE	No declaration needed
Environmental Information	2CPC100001X0201
Instructions and Manuals	2CPC119660M5601 2CPC016708M5601

Classifications

ETIM 4	EC000058 - Empty cabinet
ETIM 5	EC000058 - Empty cabinet
ETIM 6	EC000058 - Empty cabinet
ETIM 7	EC000058 - Empty cabinet
Object Classification Code	U
WEEE Category	Product Not in WEEE Scope

Categories

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Sub Distribution Boards → TwinLine N 55 - Welded

