

PRODUCT-DETAILS

UL32

UL32 flush Mounting box emty



General Information

Extended Product Type	UL32
Product ID	2CPX030755R9999
EAN	4011617307556
Catalog Description	UL32 flush Mounting box emty
Long Description	compact distribution boards, series UL, empty cabinet, for the internal use, without closed cover without door, class of protection II (double insulated), in combination with earthing set (accessory) we can achieve protection class 1, degree of protection IP30, applicable standards: EN 61439-1, EN 61439-3, Rated operational voltage 400V AC 50/60 Hz, rated current 125 A, powder-coated, in RAL 9016, enclosure out of sheet steel, without door, cable entry on top via nipple flange included, on bottom via flange opening pre-punched, dimensions in mm (H x W x D): 534 x 560 x 120, Grid unit 3 GU, panel width 2, Space units 72, without N/PE Quick-terminal, cable fastening rail integrated, pre-assembled for installation of modules and CombiLine Modules

Ordering

EAN	4011617307556
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000

Dimensions

Product Net Width	560 mm
Product Net Height	534 mm
Product Net Depth /	120 mm

Length

Product Net Weight	6.264 kg
--------------------	----------

Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	580.000 mm
Package Level 1 Height	525.000 mm
Package Level 1 Depth / Length	145.000 mm
Package Level 1 Gross Weight	6.515 kg
Package Level 1 EAN	4011617307556
Package Level 2 Units	pallet (lift) 20 piece
Package Level 2 Width	830.000 mm
Package Level 2 Height	1640.000 mm
Package Level 2 Depth / Length	1200.000 mm
Package Level 2 Gross Weight	292 kg

Additional Information

Color	traffic white
Configuration Type	pre-assembled for installation of modules and CombiLine Modules
Cover Plate Type	optional
Degree of Protection	IP30
DIN Place Units	72
Enclosure Type	compact distribution boards
Field Width	2
Housing Material	Steel
Interior Depth	120 mm
Meter Boards	0
Mounting Type	Flush-mounted
Number of Rows	3
Operational Voltage	400 V
Product Main Type	UL
Product Name	UL32 flush Mounting box empty
Protection Class	Isolated
Rated Current (I _N)	125 A
Rated Operational Voltage	Maximum 400 V
Standards	DIN EN 61439-3
Terminal Type	Quick-Terminal

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	2CPC000001C0101 2CPC000002C0101 2CPC000031C0101 2CPC000187C0101 2CPC000188C0101
Declaration of Conformity - CE	No declaration needed
Environmental Information	2CPC100001X0201
Instructions and Manuals	2CPC100502M5601

Classifications

ETIM 4	EC000214 - Small distribution board
ETIM 5	EC000214 - Small distribution board
ETIM 6	EC000214 - Small distribution board
ETIM 7	EC000214 - Small distribution board
Object Classification Code	U
WEEE Category	Product Not in WEEE Scope

Categories

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Compact Distribution Boards - Modules Assembled

