

PRODUCT-DETAILS

# UK660N4

## UK660N4 con. unit fl 60M IP30 w. door



### General Information

Extended Product Type	UK660N4
Product ID	2CPX031373R9999
EAN	4011617313731
Catalog Description	UK660N4 con. unit fl 60M IP30 w. door

### Long Description

Consumer unit, series UK600, for the internal use, with closed doorframe and door, class of protection II (double insulated), degree of protection IP30, applicable standards: EN 60670-24, IK code 07, Rated operational voltage 400V AC 50/60 Hz, rated current 63 A, Glow wire resistance 850°C, powder-coated, in RAL 9016, enclosure out of thermoplast, with trim frame and metal door, door out of sheet steel, in RAL 9016, with TIP-in closure, door opening angle 120 degree, door hinge right or left, cable entry on top via cable entry slide part is pre-punched, on bottom via cable entry slide part is pre-punched, on side via pre-punched, rear wall pre-punched, dimensions in mm (H x W x D): 872 x 384 x 97, Shutter frame dimensions in mm (H x W x D): 872 x 384 x 9, 5-rows, Space units 60, Row distance in mm: 125, covers out of Plastic, 90 degree press and turn closure, with N/PE Quick-terminal, cable fastening rail integrated, assembled with device carrier, device support removable

### Ordering

E-Number (Sweden)	2201244
EAN	4011617313731
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000

### Dimensions

Product Net Width	384 mm
Product Net Height	872 mm
Product Net Depth / Length	97 mm
Product Net Weight	5.869 kg

### Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	390.000 mm
Package Level 1 Height	880.000 mm
Package Level 1 Depth / Length	115.000 mm
Package Level 1 Gross Weight	6.104 kg
Package Level 1 EAN	4011617313731
Package Level 2 Units	pallet (lift) 30 piece
Package Level 2 Width	800.000 mm
Package Level 2 Height	1820.000 mm
Package Level 2 Depth / Length	1200.000 mm
Package Level 2 Gross Weight	196.07 kg

### Additional Information

Color	traffic white
Configuration Type	assembled with device carrier
Cover Plate Type	Door
Degree of Protection	IP30
DIN Place Units	60
Enclosure Type	Consumer unit
Housing Material	Plastic
Interior Depth	75 mm
Mounting Type	Flush-mounted
Niche Depth	95 mm
Niche Height	855 mm
Niche Width	367 mm
Number of Rows	5
Operational Voltage	400 V
Power Loss	$\Delta t = 30K$ 69 W
Product Main Type	UK
Product Name	UK660N4 con. unit fl 60M IP30 w. door
Protection Class	Isolated
Rated Current ( $I_n$ )	63 A
Rated Operational Voltage	Maximum 400 V
Spacing	125 mm
Standards	DIN 43871
Terminal Type	Quick-Terminal

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	2CPC000001C0101 2CPC000002C0101
-----------------------------------	------------------------------------

2CPC000031C0101  
2CPC000187C0101  
2CPC000188C0101

Declaration of Conformity  
- CE

No declaration needed

Instructions and Manuals

2CPC129380M5601

---

## Classifications

---

ETIM 5	EC000214 - Small distribution board
ETIM 6	EC000214 - Small distribution board
ETIM 7	EC000214 - Small distribution board
Object Classification Code	U
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

---

## Categories

---

Low Voltage Products and Systems → Enclosures → Consumer Units → Consumer Units

