

## PRODUCT-DETAILS

# UK636MV

## UK636MV media unit fl patch 3R vent



### General Information

|                       |                                     |
|-----------------------|-------------------------------------|
| Extended Product Type | UK636MV                             |
| Product ID            | 2CPX031384R9999                     |
| EAN                   | 4011617313847                       |
| Catalog Description   | UK636MV media unit fl patch 3R vent |

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Long Description | Multimedia unit, series UK600, for the internal use, with closed doorframe and door, class of protection II (double insulated), degree of protection IP30, applicable standards: EN 60670-24, IK code 07, Rated operational voltage 400V AC 50/60 Hz, rated current 63 A, Glow wire resistance 850°C, powder-coated, in RAL 9016, enclosure out of thermoplast, with frame and ventilated door, door out of sheet steel, in RAL 9016, with TIP-in closure, door opening angle 120 degree, door hinge right or left, cable entry on top via cable entry slide part is pre-punched, on bottom via cable entry slide part is pre-punched, on side via pre-punched, rear wall pre-punched, dimensions in mm (H x W x D): 622 x 384 x 97, Shutter frame dimensions in mm (H x W x D): 622 x 384 x 9, 3-rows, cable fastening rail integrated, assembled with perforated sheet steel mounting plate, patchpanel an rotatable tripple socket outlet |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Ordering

|                        |               |
|------------------------|---------------|
| E-Number (Sweden)      | 2201260       |
| EAN                    | 4011617313847 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85381000      |

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 384 mm   |
| Product Net Height         | 622 mm   |
| Product Net Depth / Length | 97 mm    |
| Product Net Weight         | 4.018 kg |

## Container Information

|                                |                        |
|--------------------------------|------------------------|
| Package Level 1 Units          | pack 1 piece           |
| Package Level 1 Width          | 390.000 mm             |
| Package Level 1 Height         | 630.000 mm             |
| Package Level 1 Depth / Length | 115.000 mm             |
| Package Level 1 Gross Weight   | 4.179 kg               |
| Package Level 1 EAN            | 4011617313847          |
| Package Level 2 Units          | pallet (lift) 45 piece |
| Package Level 2 Width          | 800.000 mm             |
| Package Level 2 Height         | 1820.000 mm            |
| Package Level 2 Depth / Length | 1200.000 mm            |
| Package Level 2 Gross Weight   | 200.81 kg              |

## Additional Information

|                           |                                                                                                     |
|---------------------------|-----------------------------------------------------------------------------------------------------|
| Color                     | traffic white                                                                                       |
| Configuration Type        | assembled with perforated sheet steel mounting plate, patchpanel an rotatable tripple socket outlet |
| Cover Plate Type          | Door                                                                                                |
| Degree of Protection      | IP30                                                                                                |
| Enclosure Type            | Multimedia unit                                                                                     |
| Housing Material          | Plastic                                                                                             |
| Interior Depth            | 81 mm                                                                                               |
| Mounting Type             | Flush-mounted                                                                                       |
| Niche Depth               | 95 mm                                                                                               |
| Niche Height              | 605 mm                                                                                              |
| Niche Width               | 367 mm                                                                                              |
| Number of Rows            | 3                                                                                                   |
| Operational Voltage       | 400 V                                                                                               |
| Power Loss                | $\Delta t = 30K$ 114 W                                                                              |
| Product Main Type         | UK                                                                                                  |
| Product Name              | UK636MV media unit fl patch 3R vent                                                                 |
| Protection Class          | Isolated                                                                                            |
| Rated Current ( $I_n$ )   | 63 A                                                                                                |
| Rated Operational Voltage | Maximum 400 V                                                                                       |
| Standards                 | DIN 43871                                                                                           |

|               |              |
|---------------|--------------|
| Terminal Type | No Terminals |
|---------------|--------------|

Certificates and Declarations (Document Number)

|                                   |                       |
|-----------------------------------|-----------------------|
| Data Sheet, Technical Information | 2CPC000001C0101       |
|                                   | 2CPC000002C0101       |
|                                   | 2CPC000031C0101       |
|                                   | 2CPC000187C0101       |
|                                   | 2CPC000188C0101       |
| Declaration of Conformity - CE    | No declaration needed |
| Instructions and Manuals          | 2CPC130102M5601       |

Classifications

|                            |                                                             |
|----------------------------|-------------------------------------------------------------|
| ETIM 5                     | EC000214 - Small distribution board                         |
| ETIM 6                     | EC000214 - Small distribution board                         |
| ETIM 7                     | EC000214 - Small distribution board                         |
| Object Classification Code | U                                                           |
| WEEE Category              | 4. Large Equipment (Any External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Enclosures → Consumer Units → Consumer Units

