

PRODUCT-DETAILS

UK636MW

UK636MW media unit fl patch 3R wifi



General Information

Extended Product Type	UK636MW
Product ID	2CPX031387R9999
EAN	4011617313878
Catalog Description	UK636MW media unit fl patch 3R wifi
Long Description	Multimedia unit, series UK600, for the internal use, with closed doorframe and door, class of protection II (double insulated), degree of protection IP30, applicable standards: EN 60670-24, IK code 07, Rated operational voltage 400V AC 50/60 Hz, rated current 63 A, Glow wire resistance 850°C, powder-coated, in RAL 9016, enclosure out of thermoplast, with frame and ventilated wifi door, door out of sheet steel, in RAL 9016, with TIP-in closure, door opening angle 120 degree, door hinge right or left, cable entry on top via cable entry slide part is pre-punched, on bottom via cable entry slide part is pre-punched, on side via pre-punched, rear wall pre-punched, dimensions in mm (H x W x D): 622 x 384 x 97, Shutter frame dimensions in mm (H x W x D): 622 x 384 x 9, 3-rows, cable fastening rail integrated, assembled with perforated sheet steel mounting plate, patchpanel an rotatable tripple socket outlet

Ordering

E-Number (Sweden)	2201261
EAN	4011617313878
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000

Dimensions

Product Net Width	384 mm
Product Net Height	622 mm
Product Net Depth / Length	97 mm
Product Net Weight	3.835 kg

Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	390.000 mm
Package Level 1 Height	630.000 mm
Package Level 1 Depth / Length	115.000 mm
Package Level 1 Gross Weight	3.988 kg
Package Level 1 EAN	4011617313878
Package Level 2 Units	pallet (lift) 45 piece
Package Level 2 Width	800.000 mm
Package Level 2 Height	1820.000 mm
Package Level 2 Depth / Length	1200.000 mm
Package Level 2 Gross Weight	192.575 kg

Additional Information

Color	traffic white
Configuration Type	assembled with perforated sheet steel mounting plate, patchpanel an rotatable tripple socket outlet
Cover Plate Type	Door
Degree of Protection	IP30
Enclosure Type	Multimedia unit
Housing Material	Plastic
Interior Depth	81 mm
Mounting Type	Flush-mounted
Niche Depth	95 mm
Niche Height	605 mm
Niche Width	367 mm
Number of Rows	3
Operational Voltage	400 V
Power Loss	$\Delta t = 30K$ 114 W
Product Main Type	UK
Product Name	UK636MW media unit fl patch 3R wifi
Protection Class	Isolated
Rated Current (I_n)	63 A
Rated Operational Voltage	Maximum 400 V
Standards	DIN 43871

Terminal Type	No Terminals
---------------	--------------

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	2CPC000001C0101
	2CPC000002C0101
	2CPC000031C0101
	2CPC000187C0101
	2CPC000188C0101
Declaration of Conformity - CE	No declaration needed
Instructions and Manuals	2CPC130102M5601

Classifications

ETIM 5	EC000214 - Small distribution board
ETIM 6	EC000214 - Small distribution board
ETIM 7	EC000214 - Small distribution board
Object Classification Code	U
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Enclosures → Consumer Units → Consumer Units

