

PRODUCT-DETAILS

UK630MV

UK630MV media unit fl DIN 3R vent do



General Information

Extended Product Type	UK630MV
Product ID	2CPX031391R9999
EAN	4011617313915
Catalog Description	UK630MV media unit fl DIN 3R vent do

Long Description	Multimedia unit, series UK600, for the internal use, with closed doorframe and door, class of protection II (double insulated), degree of protection IP30, applicable standards: EN 60670-24, IK code 07, Rated operational voltage 400V AC 50/60 Hz, rated current 63 A, Glow wire resistance 850°C, powder-coated, in RAL 9016, enclosure out of thermoplast, with frame and ventilated door, door out of sheet steel, in RAL 9016, with TIP-in closure, door opening angle 120 degree, door hinge right or left, cable entry on top via cable entry slide part is pre-punched, on bottom via cable entry slide part is pre-punched, on side via pre-punched, rear wall pre-punched, dimensions in mm (H x W x D): 872 x 384 x 97, Shutter frame dimensions in mm (H x W x D): 622 x 384 x 9, 3-rows, cable fastening rail integrated, assembled with DIN rail, perforated sheet steel mounting plate and rotatable double socket outlet
------------------	---

Ordering

E-Number (Sweden)	2201258
EAN	4011617313915
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000

Dimensions

Product Net Width	384 mm
Product Net Height	872 mm
Product Net Depth / Length	97 mm
Product Net Weight	3.875 kg

Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	390.000 mm
Package Level 1 Height	630.000 mm
Package Level 1 Depth / Length	115.000 mm
Package Level 1 Gross Weight	4.03 kg
Package Level 1 EAN	4011617313915
Package Level 2 Units	pallet (lift) 45 piece
Package Level 2 Width	800.000 mm
Package Level 2 Height	1820.000 mm
Package Level 2 Depth / Length	1200.000 mm
Package Level 2 Gross Weight	194.375 kg

Additional Information

Color	traffic white
Configuration Type	assembled with DIN rail, perforated sheet steel mounting plate and rotatable double socket outlet
Cover Plate Type	Door
Degree of Protection	IP30
Enclosure Type	Multimedia unit
Housing Material	Plastic
Interior Depth	81 mm
Mounting Type	Flush-mounted
Niche Depth	95 mm
Niche Height	605 mm
Niche Width	367 mm
Number of Rows	3
Operational Voltage	400 V
Power Loss	$\Delta t = 30K$ 114 W
Product Main Type	UK
Product Name	UK630MV media unit fl DIN 3R vent do
Protection Class	Isolated
Rated Current (I_n)	63 A
Rated Operational Voltage	Maximum 400 V
Standards	DIN 43871

Terminal Type	No Terminals
---------------	--------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	No declaration needed
Instructions and Manuals	2CPC130102M5601

Classifications

ETIM 5	EC000214 - Small distribution board
ETIM 6	EC000214 - Small distribution board
ETIM 7	EC000214 - Small distribution board
Object Classification Code	U
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Enclosures → Consumer Units → Consumer Units

