

PRODUCT-DETAILS

UK636MB

UK636MB media unit fl DIN 3R base



General Information

Extended Product Type	UK636MB
Product ID	2CPX031395R9999
EAN	4011617313953
Catalog Description	UK636MB media unit fl DIN 3R base
Long Description	Multimedia unit, series UK600, for the internal use, without closed cover without door, class of protection II (double insulated), degree of protection IP30, applicable standards: EN 60670-24, IK code 07, Rated operational voltage 400V AC 50/60 Hz, rated current 63 A, Glow wire resistance 850°C, in RAL 9016, enclosure out of thermoplast, without cover and without door, cable entry on top via cable entry slide part is pre-punched, on bottom via cable entry slide part is pre-punched, on side via pre-punched, rear wall pre-punched, dimensions in mm (H x W x D): 597 x 362 x 97, 3-rows, cable fastening rail integrated, assembled with perforated sheet steel mounting plate and DIN rail

Ordering

E-Number (Sweden)	2201259
EAN	4011617313953
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000

Dimensions

Product Net Width	362 mm
Product Net Height	597 mm

Product Net Depth / Length	97 mm
Product Net Weight	2.043 kg

Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	390.000 mm
Package Level 1 Height	630.000 mm
Package Level 1 Depth / Length	115.000 mm
Package Level 1 Gross Weight	2.125 kg
Package Level 1 EAN	4011617313953
Package Level 2 Units	pallet (lift) 45 piece
Package Level 2 Width	800.000 mm
Package Level 2 Height	1820.000 mm
Package Level 2 Depth / Length	1200.000 mm
Package Level 2 Gross Weight	111.935 kg

Additional Information

Color	traffic white
Configuration Type	assembled with perforated sheet steel mounting plate and DIN rail
Cover Plate Type	optional
Degree of Protection	IP30
Enclosure Type	Multimedia unit
Housing Material	Plastic
Interior Depth	81 mm
Mounting Type	Flush-mounted
Niche Depth	95 mm
Niche Height	605 mm
Niche Width	367 mm
Number of Rows	3
Operational Voltage	400 V
Product Main Type	UK
Product Name	UK636MB media unit fl DIN 3R base
Protection Class	Isolated
Rated Current (I _N)	63 A
Rated Operational Voltage	Maximum 400 V
Standards	DIN 43871
Terminal Type	No Terminals

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	2CPC000001C0101 2CPC000002C0101 2CPC000031C0101 2CPC000187C0101 2CPC000188C0101
Declaration of Conformity - CE	No declaration needed
Instructions and Manuals	2CPC130102M5601

Classifications

ETIM 5	EC000214 - Small distribution board
ETIM 6	EC000214 - Small distribution board
ETIM 7	EC000214 - Small distribution board
Object Classification Code	U
WEEE Category	Product Not in WEEE Scope

Categories

Low Voltage Products and Systems → Enclosures → Consumer Units → Consumer Units

