


PRODUCT-DETAILS

2VOKA

2VOKA Distribution Board 2 PW



General Information

Extended Product Type	2V0KA
Product ID	2CPX037594R9999
EAN	4011617375944
Catalog Description	2VOK A Distribution Board 2 DW

Long Description

Interior fitting system, Distribution panels, mounted on EDF-Profile, for DIN rail devices and DIN rail terminals, Grid unit 4 GU = 600 mm, panel width 2 = 500 mm, 96 Space units, Row distance in mm: 125, assembled with DIN rail 35 x 15 mm with perforation for wire holders, covers out of Plastic, 90 degree press and turn closure, RAL 7035, Design of the cover: with cut-out, usuable as of the cabinet depth of 120 mm. distribution panels or combinations must have the same grid units as the

mm, distribution panels or combinations must have the same grid units as the cabinets, in which they are installed. For floor standing and switch gear cabinets, two panels or combinations must be installed next to each other. The EDF profile rails are included in the scope of delivery.

Ordering

EAN	4011617375944
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000

Dimensions

Product Net Width	500 mm
Product Net Height	600 mm
Product Net Depth /	120 mm

Length

Product Net Weight	3 645 ka

Container Information	
Package Level 1 Units	pack 1 piece
Package Level 1 Width	505.000 mm
Package Level 1 Height	55.000 mm
Package Level 1 Depth / Length	600.000 mm
Package Level 1 Gross Weight	3.952 kg
Package Level 1 EAN	4011617375944
Package Level 2 Units	pallet (lift) 56 piece
Package Level 2 Width	800.000 mm
Package Level 2 Height	1650.000 mm
Package Level 2 Depth / Length	1200.000 mm
Package Level 2 Gross Weight	293.4 kg

Additional Information	
Cover Plate Type	With notch
Design	EDF distribution panel
DIN Place Units	96
Enclosure Type	Interior fitting system
Enclosure Type of Height	0
Field Width	2
Interior Depth	160 mm
Meter Boards	0
Module Function	DIN rail devices and DIN rail terminals
Number of Rows	3
Operational Voltage	400 V
Product Main Type	2
Product Name	2V0KA Distribution Board 2 PW
Rated Current (I _n)	400 A
Rated Operational Voltage	Maximum 400 V
Spacing	125 mm
Standards	DIN 43880
Terminal Type	Quick-Terminal

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	2CPC000001C0101 2CPC000002C0101
Declaration of Conformity - CE	No declaration needed
Environmental Information	2CPC100001X0201
Instructions and Manuals	2CPC000186C0201

Classifications

ETIM 4	EC000264 - Panel for distribution board

ETIM 5	EC000264 - Panel for distribution board
ETIM 6	EC000264 - Panel for distribution board
ETIM 7	EC000264 - Panel for distribution board
Object Classification	U
Code	
WEEE Category	Product Not in WEEE Scope

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Enclosures \rightarrow Sub\ Distribution\ Boards \rightarrow Sub\ Distribution\ Boards$

