PRODUCT-DETAILS

# ED62KA

## ED62KA Combin. Set 2F.Terminal Mo




### General Information

| | |
|---|---|
| Extended Product Type | ED62KA |
| Product ID | 2CPX037823R9999 |
| EAN | 4011617378235 |
| Catalog Description | ED62KA Combin. Set 2F.Terminal Mo |
| Long Description | Interior fitting system, Combi-Sets, mounted on EDF-Profile, for DIN rail for terminals horizontal, Grid unit 2 GU = 300 mm, panel width 2 = 500 mm, 48 Space units, Row distance in mm: 150, assembled with DIN rail 35 x 7,5 mm with perforation for wire holders, covers out of Plastic, 90 degree press and turn closure, RAL 7035, usuable as of the cabinet depth of 200 mm, combination sets are plugged into the distributor panel at the top or bottom, and mounted on the other side of the cabinet. The EDF profiles and field connectors are included in the scope of delivery. |

### Ordering

| | |
|---|---|
| EAN | 4011617378235 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85371098 |

### Dimensions

| | |
|---|---|
| Product Net Width | 500 mm |
| Product Net Height | 300 mm |
| Product Net Depth / Length | 200 mm |
| Product Net Weight | 2.47 kg |

## Container Information

| | |
|---|---|
| Package Level 1 Units | pack 1 piece |
| Package Level 1 Width | 530.000 mm |
| Package Level 1 Height | 150.000 mm |
| Package Level 1 Depth / Length | 370.000 mm |
| Package Level 1 Gross Weight | 2.569 kg |
| Package Level 1 EAN | 4011617378235 |
| Package Level 2 Units | 12 piece |
| Package Level 2 Width | 830 mm |
| Package Level 2 Height | 1710 mm |
| Package Level 2 Depth / Length | 1210 mm |

## Additional Information

| | |
|---|---|
| Design | EDF combi set |
| DIN Place Units | 48 |
| Enclosure Type | Interior fitting system |
| Enclosure Type of Height | 000 |
| Field Width | 2 |
| Interior Depth | 160 mm |
| Meter Boards | 0 |
| Module Function | DIN rail for terminals horizontal |
| Number of Rows | 0 |
| Operational Voltage | 400 V |
| Product Main Type | ED |
| Product Name | ED62KA Combin. Set 2F.Terminal Mo |
| Rated Current ($I_n$) | 400 A |
| Rated Operational Voltage | Maximum 400 V |
| Spacing | 150 mm |

## Certificates and Declarations (Document Number)

| | |
|---|---|
| Data Sheet, Technical Information | 2CPC000001C0101<br>2CPC000002C0101 |
| Declaration of Conformity - CE | No declaration needed |
| Environmental Information | 2CPC100001X0201 |
| Instructions and Manuals | 2CPC000186C0201 |

## Classifications

| | |
|---|---|
| ETIM 4 | EC000264 - Panel for distribution board |
| ETIM 5 | EC000264 - Panel for distribution board |
| ETIM 6 | EC001894 - Distributor assembly terminal blocks |
| ETIM 7 | EC001894 - Distributor assembly terminal blocks |
| Object Classification Code | U |
| WEEE Category | Product Not in WEEE Scope |

## Categories

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Sub Distribution Boards