

PRODUCT-DETAILS

ZH55

ZH55 Busbar System



General Information

Extended Product Type	ZH55
Product ID	2CPX038559R9999
EAN	4011617385592
Catalog Description	ZH55 Busbar System
Long Description	busbars as busbar system, dimensions: 20 x 5 mm, with a length of 370 mm, dimensions: 20 x 5 mm, Screw connectors M8, for a rated current of 320 A, N/PE-busbar system, 3-pole, packaging unit 1 piece

Ordering

EAN	4011617385592
Minimum Order Quantity	1 piece
Customs Tariff Number	85369001

Dimensions

Product Net Width	370 mm
Product Net Height	180 mm
Product Net Depth / Length	100 mm
Product Net Weight	1.99 kg

Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	180.000 mm
Package Level 1 Height	100.000 mm
Package Level 1 Depth / Length	370.000 mm
Package Level 1 Gross Weight	2.07 kg
Package Level 1 EAN	4011617385592
Package Level 2 Units	12 piece
Package Level 2 Width	830 mm
Package Level 2 Height	1710 mm
Package Level 2 Depth / Length	1210 mm

Additional Information

DIN Place Units	0
Enclosure Type	N/PE-busbar system
Material	Copper
Meter Boards	0
Number of Poles	3
Product Main Type	ZH
Product Name	ZH55 Busbar System
Rated Current (I _N)	320 A
Rated Service Short-Circuit Breaking Capacity (I _{CS})	25 kA
Standards	DIN 43673-1
Suitable For	1T0A 1T1A 1T2A 1T3A 1T4A 1T5A
Surface Finishing	Untreated

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	2CPC000001C0101 2CPC000002C0101
Declaration of Conformity - CE	No declaration needed
Environmental Information	2CPC100001X0201
Instructions and Manuals	2CPC000186C0201

Classifications

ETIM 4	EC002625 - Mounting accessories (switchgear cabinet)
ETIM 5	EC001900 - Busbar system for distribution boards
ETIM 6	EC001900 - Busbar system for distribution boards
ETIM 7	EC001900 - Busbar system for distribution boards
Object Classification Code	U
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Sub Distribution Boards

