

PRODUCT-DETAILS

2/2UF2021

2/2UF2021 Flush m. wall cabinet 90min.



General Information

Extended Product Type	2/2UF2021
Product ID	2CPX040088R9999
EAN	4011617400882
Catalog Description	2/2UF2021 Flush m. wall cabinet 90min.
Long Description	Fire resistance - wall cabinet, series UF, empty cabinet, for the internal use, with Door, class of protection II (double insulated), degree of protection IP41, fire resistance 90 min tested according to , Reduce fire load 90 min in line with , Maintain functionality 90 min in line with , Rated operational voltage 400V AC 50/60 Hz, surface-coated, in RAL 7035, enclosure out of non flammable material, single-leaf door, door out of non flammable material, with Swivel handle with half cylinder, door opening angle 180 degree, door hinge right, cable entry on top via fire stop cable entry, on bottom via fire stop cable entry, dimensions in mm (H x W x D): 982 x 582 x 205, Grid unit 6 GU, Overall height 2, panel width 2, Space units 144, pre-assembled for installation with Modules, Combi-Sets, CombiLine-Module on EDF-mounting frame

Ordering

EAN	4011617400882
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000

Dimensions

Product Net Width	582 mm
Product Net Height	982 mm

Product Net Depth / Length	205 mm
Product Net Weight	82 kg

Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	982.000 mm
Package Level 1 Height	582.000 mm
Package Level 1 Depth / Length	205.000 mm
Package Level 1 Gross Weight	82 kg
Package Level 1 EAN	4011617400882
Package Level 2 Units	12 piece
Package Level 2 Width	830 mm
Package Level 2 Height	1710 mm
Package Level 2 Depth / Length	1210 mm

Additional Information

Color	light grey
Configuration Type	pre-assembled for installation with Modules, Combi-Sets, CombiLine-Module on EDF-mounting frame
Cover Plate Type	None
Degree of Protection	IP41
DIN Place Units	144
Enclosure Type	Fire resistance - wall cabinet
Enclosure Type of Height	2
Field Width	2
Interior Depth	118 mm
Meter Boards	0
Mounting Type	Flush-mounted
Number of Rows	6
Operational Voltage	400 V
Product Main Type	UF
Product Name	2/2UF2021 Flush m. wall cabinet 90min.
Protection Class	Isolated
Rated Operational Voltage	Maximum 400 V

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	2CPC000001C0101 2CPC000002C0101
Declaration of Conformity - CE	No declaration needed
Environmental Information	2CPC100001X0201
Instructions and Manuals	2CPC000186C0201

Classifications

ETIM 4	EC000058 - Empty cabinet
ETIM 5	EC000058 - Empty cabinet

ETIM 6	EC000058 - Empty cabinet
ETIM 7	EC000058 - Empty cabinet
Object Classification Code	U
WEEE Category	Product Not in WEEE Scope

Categories

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Fire Resistant Enclosures

