

## PRODUCT-DETAILS

# 3/9SF302

## 3/9SF302 floor stand cab.fire prod30mi



### General Information

|                       |                                        |
|-----------------------|----------------------------------------|
| Extended Product Type | 3/9SF302                               |
| Product ID            | 2CPX043308R9999                        |
| EAN                   | 4011617433088                          |
| Catalog Description   | 3/9SF302 floor stand cab.fire prod30mi |

### Long Description

Fire resistance - floorstanding, series SF, empty cabinet, for the internal use, with door and plinth, class of protection II (double insulated), degree of protection IP44, material according to A2 — not flammable, EN 13501-1, fire resistance 30 min tested according to , Reduce fire load 30 min in line with , Maintain functionality 30 min in line with , Rated operational voltage 400V AC 50/60 Hz, surface-coated, in RAL 7035, enclosure out of non flammable material, single-leaf door, door out of non flammable material, with Swivel handle with half cylinder, door opening angle 180 degree, door hinge right, cable entry on top via fire stop cable entry, on bottom via fire stop cable entry, dimensions in mm (H x W x D): 2198 x 898 x 349, Grid unit 13 GU, Overall height 9, panel width 3, Space units 432, pre-assembled for installation with Modules, Combi-Sets, CombiLine-Module on EDF-mounting frame

### Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 4011617433088 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85381000      |

### Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 898 mm  |
| Product Net Height         | 2198 mm |
| Product Net Depth / Length | 349 mm  |
| Product Net Weight         | 278 kg  |

## Container Information

|                                |                       |
|--------------------------------|-----------------------|
| Package Level 1 Units          | pack 1 piece          |
| Package Level 1 Width          | 898.000 mm            |
| Package Level 1 Height         | 2198.000 mm           |
| Package Level 1 Depth / Length | 349.000 mm            |
| Package Level 1 Gross Weight   | 289.12 kg             |
| Package Level 1 EAN            | 4011617433088         |
| Package Level 2 Units          | pallet (lift) 1 piece |
| Package Level 2 Width          | 800.000 mm            |
| Package Level 2 Height         | 2400.000 mm           |
| Package Level 2 Depth / Length | 1200.000 mm           |

## Additional Information

|                           |                                                                                                 |
|---------------------------|-------------------------------------------------------------------------------------------------|
| Color                     | light grey                                                                                      |
| Configuration Type        | pre-assembled for installation with Modules, Combi-Sets, CombiLine-Module on EDF-mounting frame |
| Cover Plate Type          | None                                                                                            |
| Degree of Protection      | IP44                                                                                            |
| DIN Place Units           | 432                                                                                             |
| Enclosure Type            | Fire resistance - floorstanding                                                                 |
| Enclosure Type of Height  | 9                                                                                               |
| Field Width               | 3                                                                                               |
| Interior Depth            | 240 mm                                                                                          |
| Mounting Type             | Floor installation                                                                              |
| Number of Rows            | 12                                                                                              |
| Operational Voltage       | 400 V                                                                                           |
| Product Main Type         | SF                                                                                              |
| Product Name              | 3/9SF302 floor stand cab.fire prod30mi                                                          |
| Protection Class          | Isolated                                                                                        |
| Rated Operational Voltage | Maximum 400 V                                                                                   |

## Certificates and Declarations (Document Number)

|                                |                       |
|--------------------------------|-----------------------|
| Declaration of Conformity - CE | No declaration needed |
|--------------------------------|-----------------------|

## Classifications

|                            |                           |
|----------------------------|---------------------------|
| ETIM 6                     | EC000058 - Empty cabinet  |
| ETIM 7                     | EC000058 - Empty cabinet  |
| Object Classification Code | U                         |
| WEEE Category              | Product Not in WEEE Scope |

Categories

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Fire Resistant Enclosures

