

## PRODUCT-DETAILS

# 2/1AF303

## 2/1AF303 Wall cabinet fire prot.90min.



### General Information

|                       |                                        |
|-----------------------|----------------------------------------|
| Extended Product Type | 2/1AF303                               |
| Product ID            | 2CPX043384R9999                        |
| EAN                   | 4011617433842                          |
| Catalog Description   | 2/1AF303 Wall cabinet fire prot.90min. |

### Long Description

Fire resistance - floorstanding, series AF, empty cabinet, for the internal use, with Door, class of protection II (double insulated), degree of protection IP44, material according to A2 – not flammable, EN 13501-1, fire resistance 90 min tested according to , Reduce fire load 90 min in line with , Maintain functionality 90 min in line with , Rated operational voltage 400V AC 50/60 Hz, surface-coated, in RAL 7035, enclosure out of non flammable material, single-leaf door, door out of non flammable material, with Swivel handle with half cylinder, door opening angle 180 degree, door hinge right, cable entry on top via fire stop cable entry, on bottom via fire stop cable entry, dimensions in mm (H x W x D): 898 x 648 x 349, Grid unit 5 GU, Overall height 1, panel width 2, Space units 108, pre-assembled for installation with Modules, Combi-Sets, CombiLine-Module on EDF-mounting frame

### Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 4011617433842 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85381000      |

### Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 648 mm |
| Product Net Height | 898 mm |

|                            |        |
|----------------------------|--------|
| Product Net Depth / Length | 349 mm |
| Product Net Weight         | 101 kg |

## Container Information

|                                |                       |
|--------------------------------|-----------------------|
| Package Level 1 Units          | pack 1 piece          |
| Package Level 1 Width          | 648.000 mm            |
| Package Level 1 Height         | 898.000 mm            |
| Package Level 1 Depth / Length | 349.000 mm            |
| Package Level 1 Gross Weight   | 105.04 kg             |
| Package Level 1 EAN            | 4011617433842         |
| Package Level 2 Units          | pallet (lift) 1 piece |
| Package Level 2 Width          | 800.000 mm            |
| Package Level 2 Height         | 1100.000 mm           |
| Package Level 2 Depth / Length | 1200.000 mm           |

## Additional Information

|                           |                                                                                                 |
|---------------------------|-------------------------------------------------------------------------------------------------|
| Color                     | light grey                                                                                      |
| Configuration Type        | pre-assembled for installation with Modules, Combi-Sets, CombiLine-Module on EDF-mounting frame |
| Cover Plate Type          | None                                                                                            |
| Degree of Protection      | IP44                                                                                            |
| DIN Place Units           | 108                                                                                             |
| Enclosure Type            | Fire resistance - floorstanding                                                                 |
| Enclosure Type of Height  | 1                                                                                               |
| Field Width               | 2                                                                                               |
| Interior Depth            | 240 mm                                                                                          |
| Mounting Type             | Surface-mounted                                                                                 |
| Number of Rows            | 4                                                                                               |
| Operational Voltage       | 400 V                                                                                           |
| Product Main Type         | AF                                                                                              |
| Product Name              | 2/1AF303 Wall cabinet fire prot.90min.                                                          |
| Protection Class          | Isolated                                                                                        |
| Rated Operational Voltage | Maximum 400 V                                                                                   |

## Certificates and Declarations (Document Number)

|                                |                       |
|--------------------------------|-----------------------|
| Declaration of Conformity - CE | No declaration needed |
|--------------------------------|-----------------------|

## Classifications

|                            |                           |
|----------------------------|---------------------------|
| ETIM 6                     | EC000058 - Empty cabinet  |
| ETIM 7                     | EC000058 - Empty cabinet  |
| Object Classification Code | U                         |
| WEEE Category              | Product Not in WEEE Scope |

---

## Categories

---

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Fire Resistant Enclosures

