

PRODUCT-DETAILS

3/9SF303

3/9SF303 Floor stand cab.fire prot90mi



General Information

Extended Product Type	3/9SF303
Product ID	2CPX043396R9999
EAN	4011617433965
Catalog Description	3/9SF303 Floor stand cab.fire prot90mi

Long Description

Fire resistance - floorstanding, series SF, empty cabinet, for the internal use, with door and plinth, class of protection II (double insulated), degree of protection IP44, material according to A2 – not flammable, EN 13501-1, fire resistance 90 min tested according to , Reduce fire load 90 min in line with , Maintain functionality 90 min in line with , Rated operational voltage 400V AC 50/60 Hz, surface-coated, in RAL 7035, enclosure out of non flammable material, single-leaf door, door out of non flammable material, with Swivel handle with half cylinder, door opening angle 180 degree, door hinge right, cable entry on top via fire stop cable entry, on bottom via fire stop cable entry, dimensions in mm (H x W x D): 2198 x 898 x 349, Grid unit 13 GU, Overall height 9, Space units 432, pre-assembled for installation with Modules, Combi-Sets, CombiLine-Module on EDF-mounting frame

Ordering

EAN	4011617433965
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000

Dimensions

Product Net Width	898 mm
Product Net Height	2198 mm

Product Net Depth / Length	349 mm
Product Net Weight	280 kg

Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	898.000 mm
Package Level 1 Height	2198.000 mm
Package Level 1 Depth / Length	349.000 mm
Package Level 1 Gross Weight	291.2 kg
Package Level 1 EAN	4011617433965
Package Level 2 Units	pallet (lift) 1 piece
Package Level 2 Width	800.000 mm
Package Level 2 Height	2400.000 mm
Package Level 2 Depth / Length	1200.000 mm

Additional Information

Color	light grey
Configuration Type	pre-assembled for installation with Modules, Combi-Sets, CombiLine-Module on EDF-mounting frame
Cover Plate Type	None
Degree of Protection	IP44
DIN Place Units	432
Enclosure Type	Fire resistance - floorstanding
Enclosure Type of Height	9
Interior Depth	240 mm
Mounting Type	Floor installation
Number of Rows	12
Operational Voltage	400 V
Product Main Type	SF
Product Name	3/9SF303 Floor stand cab.fire prot90mi
Protection Class	Isolated
Rated Operational Voltage	Maximum 400 V

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	No declaration needed
--------------------------------	-----------------------

Classifications

ETIM 6	EC000058 - Empty cabinet
ETIM 7	EC000058 - Empty cabinet
Object Classification Code	U
WEEE Category	Product Not in WEEE Scope

Categories

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Fire Resistant Enclosures

