

PRODUCT-DETAILS

A24

A24 Wall Cabinet 2PW4R PC2 IP44



General Information

Extended Product Type	A24
Product ID	2CPX052016R9999
EAN	4011617520160
Catalog Description	A24 Wall Cabinet 2PW4R PC2 IP44
Long Description	Wall-mounting cabinet, empty cabinet, for the internal use, with Door, class of protection II (double insulated), degree of protection IP44, rated current 250 A, powder-coated, in RAL 9016, enclosure out of sheet steel, metal door , door out of sheet steel, door opening angle 120 degree, cable entry on top via membrane flange mounted, on side via flange opening pre-punched, dimensions in mm (H x W x D): 650 x 550 x 215, Grid unit 4 GU, panel width 2, Space units 96, pre-assembled for installation of metering-, modules, Combi-Sets, CombiLine-Module on EDF-mounting frame

Ordering

EAN	4011617520160
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000

Dimensions

Product Net Width	550 mm
Product Net Height	650 mm
Product Net Depth / Length	215 mm

Product Net Weight	11.733 kg
--------------------	-----------

Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	600.000 mm
Package Level 1 Height	710.000 mm
Package Level 1 Depth / Length	233.000 mm
Package Level 1 Gross Weight	12.202 kg
Package Level 1 EAN	4011617520160
Package Level 2 Units	pallet (lift) 14 piece
Package Level 2 Width	825.000 mm
Package Level 2 Height	1580.000 mm
Package Level 2 Depth / Length	1200.000 mm
Package Level 2 Gross Weight	184.262 kg

Additional Information

Color	traffic white
Configuration Type	pre-assembled for installation of metering-, modules, Combi-Sets, CombiLine-Module on EDF-mounting frame
Cover Plate Type	Door
Degree of Protection	IP44
DIN Place Units	96
Enclosure Type	Wall-mounting cabinet
Field Width	2
Housing Material	Steel plate/plastic
Interior Depth	190 mm
Mounting Type	Surface mounted/recessed mounted/partially recessed mounted
Number of Rows	4
Power Loss	$\Delta t = 20K$ 56 W $\Delta t = 25K$ 74 W $\Delta t = 30K$ 92.8 W
Product Main Type	ComfortLine A
Product Name	A24 Wall Cabinet 2PW4R PC2 IP44
Protection Class	Isolated
Rated Current (I_n)	250 A
Surface Finishing	Powder coating

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	9AKK107680A4773
Instructions and Manuals	2CPC133150M5601

Classifications

ETIM 6	EC000058 - Empty cabinet
ETIM 7	EC000058 - Empty cabinet
Object Classification Code	U

Categories

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Meter Boards → ComfortLine A

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Sub Distribution Boards → ComfortLine A

