

PRODUCT-DETAILS

A15

A15 Wall Cabinet 1PW5R PC2 IP44



General Information

Extended Product Type	A15
Product ID	2CPX052020R9999
EAN	4011617520207
Catalog Description	A15 Wall Cabinet 1PW5R PC2 IP44
Long Description	Wall-mounting cabinet, series ComfortLine, empty cabinet, for the internal use, with Door, class of protection II (double insulated), degree of protection IP44, Rated operational voltage 400V AC Hz, rated current 250 A, powder-coated, in RAL 9016, enclosure out of sheet steel, metal door , door out of sheet steel, door opening angle 120 degree, cable entry on top via membrane flange mounted, on side via flange opening pre-punched, dimensions in mm (H x W x D): 800 x 300 x 215, Grid unit 5 GU, panel width 1, Space units 60, pre-assembled for installation of metering-, modules, Combi-Sets, CombiLine-Module on EDF-mounting frame

Ordering

EAN	4011617520207
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000

Dimensions

Product Net Width	300 mm
-------------------	--------

Product Net Height	800 mm
Product Net Depth / Length	215 mm
Product Net Weight	9.518 kg

Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	350.000 mm
Package Level 1 Height	860.000 mm
Package Level 1 Depth / Length	233.000 mm
Package Level 1 Gross Weight	9.899 kg
Package Level 1 EAN	4011617520207
Package Level 2 Units	pallet (lift) 25 piece
Package Level 2 Width	870.000 mm
Package Level 2 Height	1840.000 mm
Package Level 2 Depth / Length	1200.000 mm
Package Level 2 Gross Weight	257.95 kg

Additional Information

Color	traffic white
Configuration Type	pre-assembled for installation of metering-, modules, Combi-Sets, CombiLine-Module on EDF-mounting frame
Cover Plate Type	Door
Degree of Protection	IP44
DIN Place Units	60
Enclosure Type	Wall-mounting cabinet
Field Width	1
Housing Material	Steel plate/plastic
Interior Depth	190 mm
Mounting Type	Surface mounted/recessed mounted/partially recessed mounted
Number of Rows	5
Operational Voltage	400 V
Power Loss	$\Delta t = 20K$ 41.4 W $\Delta t = 25K$ 54.6 W $\Delta t = 30K$ 68.5 W
Product Main Type	ComfortLine A
Product Name	A15 Wall Cabinet 1PW5R PC2 IP44
Protection Class	Isolated
Rated Current (I_n)	250 A
Rated Operational Voltage	Maximum 400 V
Surface Finishing	Powder coating

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	9AKK107680A4773
Instructions and Manuals	2CPC133150M5601

Classifications

ETIM 6	EC000058 - Empty cabinet
ETIM 7	EC000058 - Empty cabinet
Object Classification Code	U
WEEE Category	Product Not in WEEE Scope

Categories

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Meter Boards → ComfortLine A

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Sub Distribution Boards → ComfortLine A

