

PRODUCT-DETAILS

CA38

CA38 Comp.DB 3PW 8R empty w.door



General Information

Extended Product Type	CA38
Product ID	2CPX052158R9999
EAN	4011617521587
Catalog Description	CA38 Comp.DB 3PW 8R empty w.door

Long Description	compact distribution boards, empty cabinet, for the internal use, with Door, class of protection II (double insulated), in combination with earthing set (accessory) we can achieve protection class 1, degree of protection IP44, applicable standards: EN 61439-1, EN 61439-3, Rated operational voltage 400V AC 50/60 Hz, rated current 125 A, powder-coated, in RAL 9016, enclosure out of sheet steel, metal door , door out of sheet steel, in RAL 9016, with Standard closure, door opening angle 120 degree, door hinge right and left, cable entry on top via membrane flange mounted, on bottom via flange opening pre-punched, dimensions in mm (H x W x D): 1250 x 800 x 160, Grid unit 8 GU, panel width 3, Space units 288, without N/PE Quick-terminal, cable fastening rail integrated, pre-assembled for installation of modules and CombiLine Modules
------------------	---

Ordering

EAN	4011617521587
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000

Dimensions

Product Net Width	800 mm
Product Net Height	1250 mm
Product Net Depth / Length	160 mm
Product Net Weight	23.457 kg

Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	806.000 mm
Package Level 1 Height	1252.000 mm
Package Level 1 Depth / Length	165.000 mm
Package Level 1 Gross Weight	24.395 kg
Package Level 1 EAN	4011617521587
Package Level 2 Units	pallet (lift) 4 piece
Package Level 2 Width	800.000 mm
Package Level 2 Height	1402.000 mm
Package Level 2 Depth / Length	1200.000 mm

Additional Information

Color	traffic white
Configuration Type	pre-assembled for installation of modules and CombiLine Modules
Cover Plate Type	Door
Degree of Protection	IP44
DIN Place Units	288
Enclosure Type	compact distribution boards
Field Width	3
Housing Material	Steel
Interior Depth	135.1 mm
Mounting Type	Surface-mounted
Number of Rows	8
Operational Voltage	400 V
Power Loss	$\Delta t = 20K$ 93.8 W $\Delta t = 25K$ 123.9 W $\Delta t = 30K$ 146.3 W
Product Main Type	ComfortLine Compact CA
Product Name	CA38 Comp.DB 3PW 8R empty w.door
Protection Class	Isolated
Rated Current (I_n)	125 A
Rated Operational Voltage	Maximum 400 V
Standards	DIN EN 61439-3
Terminal Type	Quick-Terminal

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	9AKK107680A4771
Instructions and Manuals	2CPC133150M5601

Classifications

ETIM 6	EC000214 - Small distribution board
ETIM 7	EC000214 - Small distribution board
Object Classification Code	U
WEEE Category	Product Not in WEEE Scope

Categories

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Compact Distribution Boards - Modules Assembled → ComfortLine Compact CA

