

PRODUCT-DETAILS

CA28B

CA28B Comp.DB 2PW 8R empty wo.door



General Information

Extended Product Type	CA28B
Product ID	2CPX052172R9999
EAN	4011617521723
Catalog Description	CA28B Comp.DB 2PW 8R empty wo.door
Long Description	compact distribution boards, empty cabinet, for the internal use, without door, class of protection II (double insulated), in combination with earthing set (accessory) we can achieve protection class 1, degree of protection IP30, applicable standards: EN 61439-1, EN 61439-3, Rated operational voltage 400V AC 50/60 Hz, rated current 125 A, powder-coated, in RAL 9016, enclosure out of sheet steel, without door, cable entry on top via membrane flange mounted, on bottom via flange opening pre-punched, dimensions in mm (H x W x D): 1250 x 550 x 160, Grid unit 8 GU, panel width 2, Space units 192, without N/PE Quick-terminal, cable fastening rail integrated, pre-assembled for installation of modules and CombiLine Modules

Ordering

EAN	4011617521723
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000

Dimensions

Product Net Width	550 mm
Product Net Height	1250 mm
Product Net Depth /	160 mm

Length

Product Net Weight	12.172 kg
--------------------	-----------

Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	556.000 mm
Package Level 1 Height	1252.000 mm
Package Level 1 Depth / Length	165.000 mm
Package Level 1 Gross Weight	12.659 kg
Package Level 1 EAN	4011617521723
Package Level 2 Units	pallet (lift) 9 piece
Package Level 2 Width	800.000 mm
Package Level 2 Height	1402.000 mm
Package Level 2 Depth / Length	1200.000 mm

Additional Information

Color	traffic white
Configuration Type	pre-assembled for installation of modules and CombiLine Modules
Cover Plate Type	optional
Degree of Protection	IP30
DIN Place Units	192
Enclosure Type	compact distribution boards
Field Width	2
Housing Material	Steel
Interior Depth	135.1 mm
Mounting Type	Surface-mounted
Number of Rows	8
Operational Voltage	400 V
Power Loss	$\Delta t = 20K$ 63.4 W $\Delta t = 25K$ 83.7 W $\Delta t = 30K$ 105 W
Product Main Type	ComfortLine Compact CA
Product Name	CA28B Comp.DB 2PW 8R empty wo.door
Protection Class	Isolated
Rated Current (I_n)	125 A
Rated Operational Voltage	Maximum 400 V
Standards	DIN EN 61439-3
Terminal Type	Quick-Terminal

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	9AKK107680A4771
Instructions and Manuals	2CPC133150M5601

Classifications

ETIM 6	EC000214 - Small distribution board
ETIM 7	EC000214 - Small distribution board

Object Classification Code	U
WEEE Category	Product Not in WEEE Scope

Categories

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Compact Distribution Boards - Modules Assembled → ComfortLine Compact CA

