

PRODUCT-DETAILS

CA15RZ1

CA15RZ1 Comp.DB 1PW 4R IE



General Information

Extended Product Type	CA15RZ1
Product ID	2CPX052278R9999
EAN	4011617522782
Catalog Description	CA15RZ1 Comp.DB 1PW 4R IE

Long Description	compact distribution boards, partly assembled cabinet, for the internal use, with Door, class of protection II (double insulated), in combination with earthing set (accessory) we can achieve protection class 1, degree of protection IP44, applicable standards: EN 61439-1, EN 61439-3, Rated operational voltage 400V AC 50/60 Hz, rated current 125 A, powder-coated, in RAL 9016, enclosure out of sheet steel, metal door , door out of sheet steel, in RAL 9016, with Standard closure, door opening angle 130 degree, door hinge right or left, cable entry on top via pre-punched, on bottom via pre-punched, dimensions in mm (H x W x D): 800 x 300 x 160, Grid unit 5 GU, panel width 1, 4-rows, Space units 48, Row distance in mm: 150, covers out of Plastic, 90 degree press and turn closure, RAL 7035, with N/PE screw terminal, cable fastening rail integrated, expanded with distributor fields, device support removable
------------------	--

Ordering

EAN	4011617522782
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000

Dimensions

Product Net Width	300 mm
Product Net Height	800 mm
Product Net Depth / Length	160 mm

Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	306.000 mm
Package Level 1 Height	802.000 mm
Package Level 1 Depth / Length	165.000 mm
Package Level 1 EAN	4011617522782
Package Level 2 Units	pallet (lift) 28 piece
Package Level 2 Width	800.000 mm
Package Level 2 Height	1800.000 mm
Package Level 2 Depth / Length	1200.000 mm

Additional Information

Color	traffic white
Configuration Type	expanded with distributor fields
Cover Plate Type	Door
Degree of Protection	IP44
DIN Place Units	48
Enclosure Type	compact distribution boards
Field Width	1
Housing Material	Steel
Interior Depth	135.1 mm
Mounting Type	Surface-mounted
Number of Rows	4
Operational Voltage	400 V
Power Loss	$\Delta t = 20K$ 37.6 W $\Delta t = 25K$ 49.7 W $\Delta t = 30K$ 62.3 W
Product Main Type	ComfortLine Compact CA
Product Name	CA15RZ1 Comp.DB 1PW 4R IE
Protection Class	Isolated
Rated Current (I_n)	125 A
Rated Operational Voltage	Maximum 400 V
Spacing	150 mm
Standards	DIN EN 61439-3
Terminal Type	Screw Terminals

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	9AKK107680A4771
Instructions and Manuals	2CPC133150M5601

Classifications

ETIM 6	EC000214 - Small distribution board
ETIM 7	EC000214 - Small distribution board
Object Classification Code	U
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Compact Distribution Boards - Modules Assembled → ComfortLine Compact CA

