

PRODUCT-DETAILS

CA46K

CA46K Comp.DB 4PW 6R term.space



General Information

Extended Product Type	CA46K
Product ID	2CPX052299R9999
EAN	4011617522997
Catalog Description	CA46K Comp.DB 4PW 6R term.space

Long Description	compact distribution boards, partly assembled cabinet, for the internal use, with Door, class of protection II (double insulated), in combination with earthing set (accessory) we can achieve protection class 1, degree of protection IP44, applicable standards: EN 61439-1, EN 61439-3, Rated operational voltage 400V AC 50/60 Hz, rated current 125 A, powder-coated, in RAL 9016, enclosure out of sheet steel, metal door , door out of sheet steel, in RAL 9016, with Standard closure, door opening angle 120 degree, door hinge right and left, cable entry on top via membrane flange mounted, on bottom via flange opening pre-punched, dimensions in mm (H x W x D): 950 x 1050 x 160, Grid unit 6 GU, panel width 4, 6 -rows, Space units 192, Row distance in mm: 125, covers out of Plastic, 90 degree press and turn closure, RAL 7035, without N/PE Quick-terminal, cable fastening rail integrated, Assembled with distribution module + terminals, device support removable
------------------	--

Ordering

E-Number (Sweden)	2300500
EAN	4011617522997
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000

Dimensions

Product Net Width	1050 mm
Product Net Height	950 mm
Product Net Depth / Length	160 mm
Product Net Weight	33 kg

Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	1056.000 mm
Package Level 1 Height	952.000 mm
Package Level 1 Depth / Length	165.000 mm
Package Level 1 Gross Weight	34.32 kg
Package Level 1 EAN	4011617522997
Package Level 2 Units	pallet (lift) 4 piece
Package Level 2 Width	800.000 mm
Package Level 2 Height	1102.000 mm
Package Level 2 Depth / Length	1200.000 mm
Package Level 2 Gross Weight	152 kg

Additional Information

Color	traffic white
Configuration Type	Assembled with distribution module + terminals
Cover Plate Type	Door
Degree of Protection	IP44
DIN Place Units	192
Enclosure Type	compact distribution boards
Field Width	4
Housing Material	Steel
Interior Depth	135.1 mm
Mounting Type	Surface-mounted
Number of Rows	6
Operational Voltage	400 V
Power Loss	$\Delta t = 20K$ 99.6 W $\Delta t = 25K$ 131.5 W $\Delta t = 30K$ 155.2 W
Product Main Type	ComfortLine Compact CA
Product Name	CA46K Comp.DB 4PW 6R term.space
Protection Class	Isolated
Rated Current (I_n)	125 A
Rated Operational Voltage	Maximum 400 V
Spacing	125 mm
Standards	DIN EN 61439-3

Terminal Type	Quick-Terminal
---------------	----------------

Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	9AKK107680A4771
Instructions and Manuals	2CPC133150M5601

Classifications	
ETIM 6	EC000214 - Small distribution board
ETIM 7	EC000214 - Small distribution board
Object Classification Code	U
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories	
Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Compact Distribution Boards - Modules Assembled → ComfortLine Compact CA	

