

PRODUCT-DETAILS

UK612EB

UK612EB con. unit fl 12M IP30 base



General Information

Extended Product Type	UK612EB
Product ID	2CPX077845R9999
EAN	4011617778455
Catalog Description	UK612EB con. unit fl 12M IP30 base
Long Description	Consumer unit, series UK600, for the internal use, without closed cover without door, class of protection II (double insulated), degree of protection IP30, applicable standards: EN 60670-24, IK code 07, Rated operational voltage 400V AC 50/60 Hz, rated current 63 A, Glow wire resistance 850°C, in RAL 9016, enclosure out of thermoplast, without cover and without door, cable entry on top via cable entry slide part is pre-punched, on bottom via cable entry slide part is pre-punched, on side via pre-punched, rear wall pre-punched, dimensions in mm (H x W x D): 347 x 362 x 97, 1-rows, Space units 12, Row distance in mm: 125, covers out of Plastic, 90 degree press and turn closure, with N/PE screw terminal, cable fastening rail integrated, assembled with device carrier, device support removable

Ordering

EAN	4011617778455
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000

Dimensions

Product Net Width	362 mm
Product Net Height	347 mm
Product Net Depth / Length	97 mm
Product Net Weight	1.5 kg

Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	390.000 mm
Package Level 1 Height	380.000 mm
Package Level 1 Depth / Length	115.000 mm
Package Level 1 Gross Weight	1.56 kg
Package Level 1 EAN	4011617778455
Package Level 2 Units	pallet (lift) 90 piece
Package Level 2 Width	800.000 mm
Package Level 2 Height	1820.000 mm
Package Level 2 Depth / Length	1200.000 mm
Package Level 2 Gross Weight	155 kg

Additional Information

Color	traffic white
Configuration Type	assembled with device carrier
Cover Plate Type	optional
Degree of Protection	IP30
DIN Place Units	12
Enclosure Type	Consumer unit
Housing Material	Plastic
Interior Depth	75 mm
Mounting Type	Flush-mounted
Niche Depth	95 mm
Niche Height	355 mm
Niche Width	367 mm
Number of Rows	1
Operational Voltage	400 V
Power Loss	$\Delta t = 30K$ 31 W
Product Main Type	UK
Product Name	UK612EB con. unit fl 12M IP30 base
Protection Class	Isolated
Rated Current (I_n)	63 A
Rated Operational Voltage	Maximum 400 V
Spacing	125 mm
Standards	DIN 43871

Terminal Type	Screw Terminals
---------------	-----------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	No declaration needed
Instructions and Manuals	2CPC130120M5601

Classifications

ETIM 5	EC000214 - Small distribution board
ETIM 6	EC000214 - Small distribution board
ETIM 7	EC000214 - Small distribution board
Object Classification Code	U
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Enclosures → Consumer Units → Consumer Units

