

PRODUCT-DETAILS

# F202 A-100/0,03 AP-R F202 A-100/0,03 AP-R Residual Current Circuit Breaker



General Information	
Extended Product Type	F202 A-100/0,03 AP-R
Product ID	2CSF202401R1900
EAN	8012542916505
Catalog Description	F202 A-100/0,03 AP-R Residual Current Circuit Breaker
Long Description	The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. This product provides the best

with some configurations for special applications. This product provides the best compromise between safety and continuity in the service, thanks to the resistance to unwanted trippings.

Technical	
Standards	IEC/EN 61008
	UL 1053
Operating Characteristic	Instantaneous (APR High Immunity)
Type of Residual Current	A type
Rated Residual Current	30 mA
Rated Current (I <sub>n</sub> )	100 A
Number of Poles	2
Power Loss	at Rated Operating Conditions per Pole 6.5 W
Rated Voltage (U <sub>r</sub> )	230 V

ated Frequency (f)	50/60 Hz
mbient Air Temperature	Operation -2555 °C
onnecting Capacity	Busbar 10 mm² Rigid 3535 mm² Flexible 3535 mm²
egree of Protection	IP2X
lectrical Endurance	10000 cycle
ounting Type	DIN rail
bject Classification Code	Q
ollution Degree	2
ated Conditional Short- ircuit Current (I <sub>nc</sub> )	10 kA
ated Insulation Voltage I <sub>i</sub> )	500 V
ated Operational Voltage	230 V AC
ridth in Number of odular Spacings	2
nvironmental	
mbient Air Temperature	Operation -2555 °C
oHS Status	Following EU Directive 2011/65/EU
echnical UL/CSA	
aximum Operating oltage UL/CSA	277 V AC
Dimensions	
roduct Net Width	0.035 m
roduct Net Height	0.085 m
roduct Net Depth / ength	0.069 m
roduct Net Weight	0.200 kg
Container Information	
ackage Level 1 Units	box 1 piece
ackage Level 1 Width	80 mm
ackage Level 1 Height	41 mm
ackage Level 1 Depth / ength	94 mm
ackage Level 1 Gross /eight	0.235 kg
ackage Level 1 EAN	8012542916505
ackage Level 2 Units	crate 6 piece
ackage Level 2 Width	246 mm
/eight ackage Level 1 EAN ackage Level 2 Units	

Package Level 2 Depth /	80 mm
Length	

Ordering	
Minimum Order Quantity	

Minimum Order Quantity	1 piece
Customs Tariff Number	85363030

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	9AKK106713A5602
Environmental Information	Refer to RoHS
Instructions and Manuals	9AKK107991A6127
RoHS Information	2CSC423001K2702

# Popular Downloads

Data Sheet, Technical	9AKK107991A8329
Instructions and Manuals	9AKK107991A6127

#### Classifications

Object Classification Code	Q
ETIM 4	EC000003 - Residual current circuit breaker (RCCB)
ETIM 5	EC000003 - Residual current circuit breaker (RCCB)
ETIM 6	EC000003 - Residual current circuit breaker (RCCB)
ETIM 7	EC000003 - Residual current circuit breaker (RCCB)

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow Residual\ Current\ Devices\ RCDs \rightarrow Residual\ Current\ Devices\ RCDs$ 

