

PRODUCT-DETAILS

CT PRO XT 100

CT PRO XT 100 Current transformer



General Information

Extended Product Type	CT PRO XT 100
Product ID	2CSG225785R1101
EAN	8012542257851
Catalog Description	CT PRO XT 100 Current transformer
Long Description	CT PRO XT 100 is used to transform primary currents to $.5A$ secondary currents for c.a. measurement instruments

Ordering

E-Number (Finland)	6701034
EAN	8012542257851
Minimum Order Quantity	1 piece
Customs Tariff Number	90303100

Dimensions

Product Net Width	45 mm
Product Net Height	26.5 mm
Product Net Depth / Length	69 mm

Product Net Weight	0.32 kg
--------------------	---------

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	0.093 m
Package Level 1 Height	0.08 m
Package Level 1 Depth / Length	0.143 m
Package Level 1 Gross Weight	0.5 kg
Package Level 1 EAN	8012542257851

Environmental

Ambient Air Temperature	Operation -5 ... +50 °C
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Additional Information

Accuracy	±1%
Cable Cross-Section	18 mm
Cable Use	Cable and Horizontal bar
Current Limit Function	FS 5
Degree of Protection	IP30
Frequency (f)	50 ... 60 Hz
Mounting Type	Through primary
Power Loss	15 W
Product Main Type	CT
Product Name	Current transformer
Rated Cross-Section	20 x 10 mm
RoHS Date	27/01/2014 0.00.00
Secondary Output Connection	Screw connection

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	9AKK107046A0430
Declaration of Conformity - CE	9AKK106713A5701
Environmental Information	See RoHS Information
Instructions and Manuals	2CSC446012B0201
RoHS Information	2CSC445004K2701

Classifications

ETIM 4

EC002048 - Current transformer

ETIM 5	EC002048 - Current transformer
ETIM 6	EC002048 - Current transformer
ETIM 7	EC002048 - Current transformer
Object Classification Code	P
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Energy Efficiency Devices → Current Transformers

