

PRODUCT-DETAILS

DS201 B10 A100

DS201 B10 A100 - RCBO



General Information

Extended Product Type	DS201 B10 A100
Product ID	2CSR255180R2105
EAN	8012542790211
Catalog Description	DS201 B10 A100 - RCBO
Long Description	The DS201 series is a 1P+N RCBO in two-modules width for the protection of end user single-phase circuits against overload and short-circuit currents; protection against the effects of sinusoidal alternating and direct pulsating earth fault currents; protection against indirect contacts and additional protection against direct contacts (with sensitivity = 30 mA).

Technical

Standards	IEC/EN 61009-1, IEC/EN 61009-2-1
Operating Characteristic	Instantaneous
Type of Residual Current	A type
Number of Poles	2
Number of Protected Poles	1
Rated Current (I_n)	10 A
Rated Current Sensitivity	0.1 A
Rated Voltage (U_r)	230 V
Rated Insulation Voltage (U_i)	500 V
Overvoltage Category	III
Pollution Degree	2

Test Voltage (U _t)	110 ... 264 V
Rated Frequency (f)	50/60 Hz
Rated Short-Circuit Capacity (I _{cn})	6 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	10 kA
Rated Service Short-Circuit Breaking Capacity (I _{cs})	7.5 kA
Rated Residual Breaking Capacity (I _{Δm})	EN 61009-1 6000 A IEC 61009-1 6000 A
Primary Rated Impulse Withstand Voltage	4 kV
Dielectric Test Voltage	2.5 kV
Tripping Characteristic	B
Energy Limiting Class	3
Housing Type	Insulation group I - II, RAL 7035
Actuator Type	Toggle - Insulation group II, Black RAL 9005, sealable in ON-OFF positions
Contact Position Indication	Red ON / Green OFF
Fault Indication	Blue flag on toggle
Electrical Endurance	10000 cycle 20000 cycle
Degree of Protection	Terminals IP20 Housing IP40
Resistance to Shock acc. to IEC 60068-2-27	25g / 2 shocks / 13 ms
Resistance to Vibrations acc. to IEC 60068-2-6	0.1 mm or 1 g - 20 cycles at 5...150...5 Hz
Environmental Conditions	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
Reference Ambient Air Temperature	30 °C
Terminal Type	Screw Terminals
Screw Terminal Type	Failsafe Bi-directional Cylinder-lift Terminal
Cable Size	25 mm ²
Connecting Capacity	Busbar 10/10 mm ² Stranded 0.75 ... 25 mm ² Flexible with Ferrule 0.75 ... 16 mm ² Flexible 0.75 ... 16 mm ²
Tightening Torque	2.8 N·m
Wire Stripping Length	12 mm
Mounting Type	on DIN rail EN 60715 (35mm) by means of mounting clip
Mounting Position	Any
Power Supply Connection	Arbitrary
Position of Neutral Terminals	Right
Power Loss	1.8 W
Number of Modular Spacings per DIN Rail	2
Accessory Type	Auxiliary contact Signal contact / auxiliary contact Shunt trip Auxiliary contact for bottom fitting Undervoltage release Overvoltage release Motor operating device

Environmental

Ambient Air Temperature

Operation -25...55 °C

Technical UL/CSA

Short-Circuit Current
Rating (SCCR)

0.1 A

Dimensions

Product Net Width	0.035 m
Product Net Height	0.085 m
Product Net Depth / Length	0.069 m
Product Net Weight	0.200 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	40 mm
Package Level 1 Height	106 mm
Package Level 1 Depth / Length	80 mm
Package Level 1 Gross Weight	225 g
Package Level 1 EAN	8012542790211
Package Level 2 Units	5 piece
Package Level 2 Width	200 mm
Package Level 2 Height	106 mm
Package Level 2 Depth / Length	80 mm
Package Level 2 Gross Weight	1125 g
Package Level 2 EAN	8012542584919

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363010
E-Number (Sweden)	2100389

Certificates and Declarations (Document Number)

ABS Certificate	9AKK107991A2823
CB Certificate	9AKK107492A6060
CCC Certificate	9AKK107492A6067
Declaration of Conformity - CE	9AKK106713A5588
DNV GL Certificate	9AKK107680A3457 9AKK107680A3456
EAC Certificate	9AKK107492A6071 9AKK107991A7755
Environmental Information	2CSC422002K2701
GOST Certificate	9AKK107992A1640

Instructions and Manuals	9AKK107492A6006
KEMA Certificate	9AKK107492A6076
ÖVE Certificate	9AKK107492A6085
RMRS Certificate	9AKK107680A3454 9AKK107680A3455
RoHS Information	2CSC422002K2701
SEV Certificate	9AKK107680A1558 9AKK107680A1560
VDE Certificate	9AKK107492A6092

Popular Downloads

Data Sheet, Technical Information	9AKK107492A6187
Instructions and Manuals	9AKK107492A6006

Classifications

Object Classification Code	Q
ETIM 6	EC000905 - Earth leakage circuit breaker
ETIM 7	EC000905 - Earth leakage circuit breaker

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Circuit Breakers with Overcurrent Protection RCBO

