

## PRODUCT-DETAILS

# DS204 M A-C13/0,03

## DS204 M A-C13/0,03 - RCB0



### General Information

|                       |                                                                                                                                                                                                                                                                        |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | DS204 M A-C13/0,03                                                                                                                                                                                                                                                     |
| Product ID            | 2CSR274101R1134                                                                                                                                                                                                                                                        |
| EAN                   | 8012542850700                                                                                                                                                                                                                                                          |
| Catalog Description   | DS204 M A-C13/0,03 - RCB0                                                                                                                                                                                                                                              |
| Long Description      | The RCBOs DS200 series has the function to protect against overload and short-circuit currents; protection against the effects of sinusoidal alternating earth fault currents; protection against indirect contacts and additional protection against direct contacts. |

### Technical

|                                                |                                  |
|------------------------------------------------|----------------------------------|
| Standards                                      | IEC/EN 60947-2<br>IEC/EN 61009-1 |
| Operating Characteristic                       | Instantaneous                    |
| Type of Residual Current                       | A type                           |
| Number of Poles                                | 4                                |
| Number of Protected Poles                      | 4                                |
| Rated Current ( $I_n$ )                        | 13 A                             |
| Rated Voltage ( $U_r$ )                        | 400 V AC                         |
| Rated Frequency (f)                            | 50/60 Hz                         |
| Rated Short-Circuit Capacity ( $I_{cn}$ )      | (400 V AC) 10 kA                 |
| Rated Ultimate Short-Circuit Breaking Capacity | (400 V AC) 15 kA                 |

(I<sub>cu</sub>)

|                               |                                                                                                  |
|-------------------------------|--------------------------------------------------------------------------------------------------|
| Tripping Characteristic       | C                                                                                                |
| Electrical Endurance          | 10000 cycle                                                                                      |
| Connecting Capacity           | Busbar 10 mm <sup>2</sup><br>Rigid 16 ...25 mm <sup>2</sup><br>Flexible 16 ...25 mm <sup>2</sup> |
| Power Supply Connection       | Arbitrary                                                                                        |
| Position of Neutral Terminals | Right                                                                                            |
| Power Loss                    | 7.7 W                                                                                            |

## Environmental

|                         |                                                    |
|-------------------------|----------------------------------------------------|
| Ambient Air Temperature | Operation -25 ... +55 °C<br>Storage -40 ... +70 °C |
|-------------------------|----------------------------------------------------|

## Technical UL/CSA

|                                     |       |
|-------------------------------------|-------|
| Short-Circuit Current Rating (SCCR) | 30 mA |
|-------------------------------------|-------|

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 105 mm   |
| Product Net Height         | 0.093 m  |
| Product Net Depth / Length | 69 mm    |
| Product Net Weight         | 0.780 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 0.49 m        |
| Package Level 1 Height         | 0.11 m        |
| Package Level 1 Depth / Length | 0.09 m        |
| Package Level 1 Gross Weight   | 0.83 kg       |
| Package Level 1 EAN            | 8012542850700 |

## Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85363030 |

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 9AKK106713A5607 |
| Environmental Information      | Refer to RoHS   |
| Instructions and Manuals       | 9AKK107045A1451 |
| RoHS Information               | 2CSC423002K2701 |

---

### Popular Downloads

---

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 9AKK107046A0424 |
| Instructions and Manuals          | 9AKK107045A1451 |

---

---

### Classifications

---

|                            |                                                           |
|----------------------------|-----------------------------------------------------------|
| Object Classification Code | Q                                                         |
| ETIM 4                     | EC002281 - Distributor assembly with combination RCCB/MCB |
| ETIM 5                     | EC002281 - Distributor assembly with combination RCCB/MCB |
| ETIM 6                     | EC002281 - Distributor assembly with combination RCCB/MCB |
| ETIM 7                     | EC002281 - Distributor assembly with combination RCCB/MCB |

---

---

### Categories

---

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Circuit Breakers with Overcurrent Protection RCBO

